


INDUSTRIAL HOSES - air and water



WS - ST WS - GI

Internal layer: Black EPDM rubber
(with increased parameters)

Reinforcement: External AISI 304 braid

Working temp.: Up to +110°C

Flexible hose assembly designed for sanitary systems (hot and cold water). Widely used in industrial installations, central heating and air-conditioning. Resistant to glycol (concentration to 35%). Available with brass fitting and stainless steel (AISI 304) ferrules. Hose assemblies with different thread types and lengths available on request. Holds technical approval to be used in construction industry.

code	I.D. [mm]	O.D. [mm]	working pressure [bar]	thread 1 [inch]	thread 2 [inch]	flow max. * [l/min.]	length [mm]			
VO-ST-06DP-06DP-020	8	13	16	3/8 female	3/8 female	29	200			
VO-ST-06DP-06DP-040							400			
VO-ST-06DP-06DP-060							600			
VO-ST-06DP-06DP-080							800			
VO-ST-06DP-06DP-100							1000			
VO-ST-08DP-08DP-020				12	20		16	1/2 female	1/2 female	200
VO-ST-08DP-08DP-040										400
VO-ST-08DP-08DP-060										600
VO-ST-08DP-08DP-080										800
VO-ST-08DP-08DP-100										1000
VO-GI-08DP-08DP-030	12	20	16	1/2 female	1/2 male	65		300		
VO-GI-08DP-08DP-040								400		
VO-GI-08DP-08DP-050								500		
VO-GI-08DP-08MP-030								300		
VO-GI-08DP-08MP-040								400		
VO-GI-08DP-08MP-050				500						
VO-GI-12DP-12DP-030				3/4 female			16	3/4 female	3/4 female	300
VO-GI-12DP-12DP-040										400
VO-GI-12DP-12DP-050										500
VO-GI-12DP-12MP-030										300
VO-GI-12DP-12MP-040	400									
VO-GI-12DP-12MP-050	500									

* - at 3 bar working pressure

