





INDUSTRIAL FITTINGS - couplings


Symmetrical couplings NOR (Norway)

picture	code	DN [mm]	lug dimension [mm]	fitting diameter [mm]	description
	GP-NOR1040038B	40	50	38	Coupling with hose tail. Material: bronze. Working press.: 10 bar. Seal: NBR.
	GP-NOR1050038B	50	66	38	
	GP-NOR1050052B	50	66	52	
	GP-NOR1065038B	65	83	38	
	GP-NOR1065052B	65	83	52	
	GP-NOR1065064B	65	83	64	

picture	code	DN [mm]	lug dimension [mm]	thread size [inch]	description
	GP-NOR2040025B	40	50	1	Coupling with BSP female thread. Material: bronze. Working press.: 10 bar. Seal: NBR.
	GP-NOR2040050B	40	50	2	
	GP-NOR2050038B	50	66	1.1/2	
	GP-NOR2050050B	50	66	2	
	GP-NOR2065038B	65	83	1.1/2	
	GP-NOR2065050B	65	83	2	
	GP-NOR2065065B	65	83	2.1/2	

picture	code	DN [mm]	lug dimension [mm]	thread size [inch]	description
	GP-NOR3040032B	40	50	1.1/4	Coupling with BSP male thread. Material: bronze. Working press.: 10 bar. Seal: NBR.
	GP-NOR3050038B	50	66	1.1/2	
	GP-NOR3050050B	50	66	2	
	GP-NOR3065038B	65	83	1.1/2	
	GP-NOR3065050B	65	83	2	
	GP-NOR3065065B	65	83	2.1/2	

picture	code	DN [mm]	lug dimension [mm]	description
	GP-NOR4040050B	40	50	Blank cap with chain. Material: aluminium. Working press.: 10 bar. Seal: NBR.
	GP-NOR4050066B	50	66	
	GP-NOR4065083B	65	83	

picture	code	DN [mm]	description
	GP-NOR5040	40	Seal. Material: NBR.
	GP-NOR5050	50	
	GP-NOR5065	65	