





CLEANING AND WASHING - low pressure


NiTO water spray guns

|  <p>NiTO LIGHT DUTY</p> | code | connection | description |
|---|------------|--------------------|--|
| | NT-28002A8 | 3/4" female thread | General purpose, lightweight, economical water spray gun with adjustable outlet nozzle, smooth flow control. Made of brass with blue polyurethane outside shield. Working press.: 7 bar. Working temp.: up to +60°C. |

|  <p>NiTO I</p> | code | connection | description |
|--|-----------------|------------------|---|
| | NT-53800A1 | 1/2" NiTO plug | General purpose, lightweight water spray gun with adjustable outlet nozzle, smooth linear flow control and trigger lock. Also available in blue, white, red, yellow and green colour. Weight: 0.295 kg. Cover body: highly durable material. Nozzle: chrome-plated brass. Working press.: 6 bar at 40°C. 4 bar at 60°C. Flow rate: 8.5 ÷ 10.5 l/min (3 bar). |
| | NT-63820A1 | 3/4" NiTO plug | |
| | NT-53802A5 | 1/2" male thread | |
| NT-59800A1 | 1/2" CLICK plug | | |





|  <p>NiTO II</p> | code | connection | description |
|---|------------|------------------------------|--|
| | NT-30550A3 | 3/4" female thread | Industrial water spray gun with adjustable outlet nozzle, smooth linear flow control and trigger lock. The cover body is impact resistant. Casing: composite material. Weight: 0.7 kg. Working press.: 25 bar. Flow rate: 20 ÷ 60 l/min (5 bar) depending on the assembled nozzle. Flow rate with standard nozzle: 40 l/min. Working temp.: up to +90°C. |
| | NT-30525A3 | 1/2" NiTO plug | |
| | NT-30500A3 | 3/4" NiTO plug | |
| | NT-30520A3 | 1" NiTO plug | |
| | NT-30530A3 | 1/2" hose tail | |
| | NT-30510A3 | 3/4" hose tail | |
| NT-30210A0 | | Nozzle set 20, 30, 60 l/min. | |

|  <p>NiTO HEAVY DUTY</p> | code | connection | description |
|---|----------------|--------------------|--|
| | NT-30000A0 | 1/2" female thread | Industrial water spray gun with adjustable outlet nozzle and linear flow control. Cover body: synthetic rubber. Weight: 1.1 kg. Working press.: up to 25 bar. Flow rate: 25 ÷ 42 l/min (5 bar). Working temp.: up to +80°C. |
| | NT-30000A3 | 3/4" hose tail | |
| | NT-30030A3 | 1/2" NiTO plug | |
| NT-30010A3 | 3/4" NiTO plug | | |



|  <p>NiTO ERGO</p> | code | connection | description |
|---|----------------|----------------|--|
| | NT-40525A3 | 1/2" NiTO plug | General purpose, ergonomic design, lightweight water spray gun with adjustable outlet nozzle, smooth linear flow control and trigger with lock function. Weight: 0.5 kg. Cover body: composite material. Nozzle: chrome-plated brass. Working press.: up to 12 bar. Working temp.: up to +80°C. Flow rate: 50 l/min (5 bar). |
| NT-40500A3 | 3/4" NiTO plug | | |


CLEANING AND WASHING - low pressure

AKBO water spray guns

| | | code | version | description |
|--|--|--------------------------|---|---|
|  AK-RN001-BL AK-RN001-W |  AK-RNP01-BL AK-RNP01-W | AK-RN001-BL | blue | HEAVY DUTY water spray gun of AISI 316 steel. Working press.: 24 bar. Working temp.: up to +95°C. |
| | | AK-RNP01-BL | blue trigger protection | |
|  AK-RNP01-W | AK-RN001-W | white | | |
| | AK-RNP01-W | white trigger protection | | |
|  AK-RHP01-R | AK-RHP01-R | red | HEAVY DUTY water spray gun of AISI 316 steel, with PTFE-air insulation. Working press.: 24 bar. Working temp.: up to +95°C. | |
| | AK-RHP02-R-L40 | red lance 40 cm | | |
| Note! <ul style="list-style-type: none"> - the guns are not designed for steam, - special precautions must be taken when the gun is used for hot water. | | | | |

Water jets

| | | code | connection | material | description |
|--|------------|--------------------|---------------------|---|-------------|
|   | NT-53750A3 | 1/2" NiTO plug | chrome-plated brass | Adjustable nozzle. Working press.: up to 25 bar. | |
| | NT-63750A3 | 3/4" NiTO plug | chrome-plated brass | | |
| | NT-20300A9 | 3/4" female thread | nickel-plated brass | | |
| | NT-20000A4 | 15/20 mm hose tail | brass | | |

| | | code | connection | description |
|---|----------------------|--------------------|---|-------------|
|  HANDFIGHTER | IN-59481-020 (short) | 3/4" male thread | An industrial water jet with adjustable outlet nozzle. The application of a safety ring made of EPDM rubber gives additional protection against mechanical damage. Material: brass Cover body: highly resistant orange plastic Nozzle: 7 mm. Working pressure: 16bar. Flow rate: 75 l/min (6 bar). | |
| | IN-59481-120 (short) | 19 mm hose tail | | |
| | IN-59481-220 (long) | 3/4" female thread | | |
| | IN-59481-225 (long) | 1" male thread | | |
| | IN-59482-020 (short) | 3/4" male thread | An industrial water jet with adjustable outlet nozzle. The application of a safety ring of EPDM rubber gives additional protection against mechanical damage. Material: brass Cover body: highly resistant red material. Nozzle: 10 mm. Working pressure: 16 bar. Flow rate: 150 l/min (6 bar). | |
| | IN-59482-125 (short) | 25 mm hose tail | | |
| | IN-59482-220 (long) | 3/4" female thread | | |
| | IN-59482-225 (long) | 1" male thread | | |