CAMLOCK couplings

Type B



CAMLOCK coupling coupler
with male thread BSPT or NPT

aluminium

brass

AISI 316 stainless steel

polypropylene

size				index (aluminium)	index (brass)	index (AISI 316 steel)	index (polypropylene)
DN [mm]	grooved [inch]	d (adaptor) [mm]	thread [inch]				
15	1/2	~ 24	1/2 BSPT	AC-B-050-A AC-B-050-AX	AC-B-050-B AC-B-050-BX	AC-B-050-SS AC-B-050-SSX	- -
20	3/4	32,1	1/2 BSPT	- -	- -	- -	AC-B-050-P -
20	3/4	32,1	3/4 BSPT	AC-B-075-A AC-B-075-AX	AC-B-075-B AC-B-075-BX	AC-B-075-SS AC-B-075-SSX	AC-B-075-P -
25	1	36,7	1.1/4 BSPT	- -	- -	- -	AC-B-125-P -
25	1	36,7	1 BSPT	AC-B-100-A AC-B-100-AX	AC-B-100-B AC-B-100-BX	AC-B-100-SS* AC-B-100-SSX	AC-B-100-P -
25	1	36,7	1 NPT	AC-B-100-A-NPT AC-B-100-AX-NPT	- -	- -	- -
32	1.1/4	45,5	1.1/4 BSPT	AC-B-125-A AC-B-125-AX	AC-B-125-B AC-B-125-BX	AC-B-125-SS* AC-B-125-SSX	- -
40	1.1/2	53,4	1 BSPT	- AC-B-150-100-AX	- -	- -	- -
40	1.1/2	53,4	1.1/2 BSPT	AC-B-150-A AC-B-150-AX	AC-B-150-B AC-B-150-BX	AC-B-150-SS* AC-B-150-SSX	AC-B-150-P -
50	2	63	1.1/2 BSPT	- AC-B-200-150-AX	- -	- -	- -
50	2	63	2 BSPT	AC-B-200-A AC-B-200-AX	AC-B-200-B AC-B-200-BX	AC-B-200-SS* AC-B-200-SSX	AC-B-200-P -
50	2	63	2 NPT	- -	- -	AC-B-200-SS-NPT AC-B-200-SSX-NPT	- -
65	2.1/2	75,8	2.1/2 BSPT	AC-B-250-A AC-B-250-AX	AC-B-250-B AC-B-250-BX	AC-B-250-SS AC-B-250-SSX	- -
80	3	91,5	2 BSPT	- AC-B-300-200-AX	- -	- -	- -
80	3	91,5	3 BSPT	AC-B-300-A AC-B-300-AX	AC-B-300-B AC-B-300-BX	AC-B-300-SS AC-B-300-SSX	AC-B-300-P -
80	3	91,5	3 NPT	AC-B-300-A-NPT AC-B-300-AX-NPT	- -	- -	- -
80	3	91,5	4 BSPT	- AC-B-300-400-AX	- -	- -	- -
100	4	119,5	3 BSPT	- AC-B-400-300-AX	- -	- -	- -
100	4	119,5	4 BSPT	AC-B-400-A AC-B-400-AX	AC-B-400-B AC-B-400-BX	AC-B-400-SS AC-B-400-SSX	AC-B-400-P -
125	5	145,6	5 BSPT	AC-B-500-A AC-B-500-AX	AC-B-500-B AC-B-500-BX	AC-B-500-SS AC-B-500-SSX	- -
150	6	176	6 BSPT	AC-B-600-A AC-B-600-AX	AC-B-600-B AC-B-600-BX	AC-B-600-SS AC-B-600-SSX	- -

* - available with E-CTFE lining, example index: AC-B-100-SSE