


CAMLOCK connectors

DC type



CAMLOCK connector plug blanking socket



aluminium



brass



stainless steel AISI 316



polypropylene

DN [mm].	size		index (aluminium)	index (brass)	index (AISI 316 steel)	index (polypropylene)
	connector [inch]	d (plug) [mm].				
15	1/2	~ 24	AC-DC-050-A AC-DC-050-AX	AC-DC-050-B AC-DC-050-BX	AC-DC-050-SS AC-DC-050-SSX	- -
20	3/4	32,1	AC-DC-075-A AC-DC-075-AX	AC-DC-075-B AC-DC-075-BX	AC-DC-075-SS AC-DC-075-SSX	AC-DC-075-P -
25	1	36,7	AC-DC-100-A AC-DC-100-AX	AC-DC-100-B AC-DC-100-BX	AC-DC-100-SS AC-DC-100-SSX	AC-DC-100-P -
32	1.1/4	45,5	AC-DC-125-A AC-DC-125-AX	AC-DC-125-B AC-DC-125-BX	AC-DC-125-SS AC-DC-125-SSX	AC-DC-125-P -
40	1.1/2	53,4	AC-DC-150-A AC-DC-150-AX	AC-DC-150-B AC-DC-150-BX	AC-DC-150-SS AC-DC-150-SSX	AC-DC-150-P -
50	2	63	AC-DC-200-A AC-DC-200-AX	AC-DC-200-B AC-DC-200-BX	AC-DC-200-SS AC-DC-200-SSX	AC-DC-200-P -
65	2.1/2	75,8	AC-DC-250-A AC-DC-250-AX	AC-DC-250-B AC-DC-250-BX	AC-DC-250-SS AC-DC-250-SSX	- -
80	3	91,5	AC-DC-300-A AC-DC-300-AX	AC-DC-300-B AC-DC-300-BX	AC-DC-300-SS AC-DC-300-SSX	AC-DC-300-P -
100	4	119,5	AC-DC-400-A AC-DC-400-AX	AC-DC-400-B AC-DC-400-BX	AC-DC-400-SS AC-DC-400-SSX	AC-DC-400-P -
125	5	145,6	AC-DC-500-A AC-DC-500-AX	AC-DC-500-B AC-DC-500-BX	AC-DC-500-SS AC-DC-500-SSX	- -
150	6	176	AC-DC-600-A AC-DC-600-AX	AC-DC-600-B AC-DC-600-BX	AC-DC-600-SS AC-DC-600-SSX	- -

Note: The chain for the cap is a separate product item.



CAMLOCK type E 3/4" aluminium connector plugs secured with blanking sockets type DC mounted to TU 25 fuel hose (SP-TU25-19) using ASFA-L 9 mm worm ties (AB-03015783) in AISI 316 stainless steel.