


CAMLOCK connectors

DP type



Blanking plug for CAMLOCK connector socket



aluminium



brass



AISI 316 steel



polypropylene

DN [mm].	size		index (aluminium)	index (brass)	index (AISI 316 steel)	index (polypropylene)
	connector [inch]	d [mm]				
15	1/2	~ 24	AC-DP-050-A AC-DP-050-AX	AC-DP-050-B AC-DP-050-BX	AC-DP-050-SS AC-DP-050-SSX	- -
20	3/4	32,1	AC-DP-075-A AC-DP-075-AX	AC-DP-075-B AC-DP-075-BX	AC-DP-075-SS AC-DP-075-SSX	AC-DP-075-P -
25	1	36,7	AC-DP-100-A AC-DP-100-AX	AC-DP-100-B AC-DP-100-BX	AC-DP-100-SS AC-DP-100-SSX	AC-DP-100-P -
32	1.1/4	45,5	AC-DP-125-A AC-DP-125-AX	AC-DP-125-B AC-DP-125-BX	AC-DP-125-SS AC-DP-125-SSX	AC-DP-125-P -
40	1.1/2	53,4	AC-DP-150-A AC-DP-150-AX	AC-DP-150-B AC-DP-150-BX	AC-DP-150-SS AC-DP-150-SSX	AC-DP-150-P -
50	2	63	AC-DP-200-A AC-DP-200-AX	AC-DP-200-B AC-DP-200-BX	AC-DP-200-SS AC-DP-200-SSX	AC-DP-200-P -
65	2.1/2	75,8	AC-DP-250-A AC-DP-250-AX	AC-DP-250-B AC-DP-250-BX	AC-DP-250-SS AC-DP-250-SSX	- -
80	3	91,5	AC-DP-300-A AC-DP-300-AX	AC-DP-300-B AC-DP-300-BX	AC-DP-300-SS AC-DP-300-SSX	AC-DP-300-P -
100	4	119,5	AC-DP-400-A AC-DP-400-AX	AC-DP-400-B AC-DP-400-BX	AC-DP-400-SS AC-DP-400-SSX	AC-DP-400-P -
125	5	145,6	AC-DP-500-A AC-DP-500-AX	AC-DP-500-B AC-DP-500-BX	AC-DP-500-SS AC-DP-500-SSX	- -
150	6	176	AC-DP-600-A AC-DP-600-AX	AC-DP-600-B AC-DP-600-BX	AC-DP-600-SS AC-DP-600-SSX	- -

Note: The chain for the cap is a separate product item.



Composite vapour hose for tanks, one end terminated with a CAMLOCK type D 3" aluminium coupling socket screwed onto a 3" BSP male thread (DT-KGZ-075-A) the other end terminated with a CAMLOCK type DVR 4" (ZP-VR-DRVR4030-A) aluminium coupling socket screwed onto a 3" BSP male thread (DT-KGZ-075-A). The CAMLOCK type D and DVR connector sockets are protected with aluminium plugs (AC-DP-300-A and AC-DP-400-A).