


**CAMLOCK connectors**

**Type E**



**CAMLOCK connector plug with corrugated hose end**



aluminium



brass



stainless steel AISI 316



polypropylene

DN [mm]	size			index (aluminium)	index (brass)	index (AISI 316 steel)	index (polypropylene)
	connector [inch]	d [mm]	Hose diameter [inch]				
15	1/2	~ 24	1/2	AC-E-050-A AC-E-050-AX	AC-E-050-B AC-E-050-BX	AC-E-050-SS AC-E-050-SSX	- -
20	3/4	32,1	1/2	-	-	-	AC-E-050-P -
20	3/4	32,1	3/4	AC-E-075-A AC-E-075-AX	AC-E-075-B AC-E-075-BX	AC-E-075-SS AC-E-075-SSX	AC-E-075-P -
25	1	36,7	1	AC-E-100-A AC-E-100-AX	AC-E-100-B AC-E-100-BX	AC-E-100-SS AC-E-100-SSX	AC-E-100-P -
25	1	36,7	1.1/4	-	-	-	AC-E-125-P -
32	1.1/4	45,5	1.1/4	AC-E-125-A AC-E-125-AX	AC-E-125-B AC-E-125-BX	AC-E-125-SS AC-E-125-SSX	- -
40	1.1/2	53,4	1.1/2	AC-E-150-A AC-E-150-AX	AC-E-150-B AC-E-150-BX	AC-E-150-SS AC-E-150-SSX	AC-E-150-P -
50	2	63	2	AC-E-200-A AC-E-200-AX	AC-E-200-B AC-E-200-BX	AC-E-200-SS AC-E-200-SSX	AC-E-200-P -
65	2.1/2	75,8	2.1/2	AC-E-250-A AC-E-250-AX	AC-E-250-B AC-E-250-BX	AC-E-250-SS AC-E-250-SSX	- -
80	3	91,5	2	- AC-E-300-200-AX	-	-	- -
80	3	91,5	3	AC-E-300-A AC-E-300-AX	AC-E-300-B AC-E-300-BX	AC-E-300-SS AC-E-300-SSX	AC-E-300-P -
100	4	119,5	3	- AC-E-400-300-AX	-	-	- -
100	4	119,5	4	AC-E-400-A AC-E-400-AX	AC-E-400-B AC-E-400-BX	AC-E-400-SS AC-E-400-SSX	AC-E-400-P -
125	5	145,6	5	AC-E-500-A AC-E-500-AX	AC-E-500-B AC-E-500-BX	AC-E-500-SS AC-E-500-SSX	- -
150	6	176	6	AC-E-600-A AC-E-600-AX	AC-E-600-B AC-E-600-BX	AC-E-600-SS AC-E-600-SSX	- -



CAMLOCK type E 3/4" polypropylene connector mounted to VACUPRESS CHEM DN19 hose (ME-VACUPRCH-019) using ASFA-L 9 mm worm bands (AB-03015783) in AISI 316 steel.



CAMLOCK type E 3/4" connector plug in AISI stainless steel 316 mounted to the BLUE 20 BAR DN19 hose (IV-BLUE20-19) using the SUPRA HEAVY DUTY screw clamp (AB-03013075) in AISI 316 steel.