

IBC connectors

<p>Adaptor 90° adjustable with female thread (swivel nut) and male thread DIN EN 12713</p> 	<p>index</p>	<p>Internal thread size DIN EN 12713</p>	<p>External thread size DIN EN 12713</p>
	<p>AC-IBMF060-K90</p>	<p>S60x6</p>	<p>S60x6</p>
<p>IBC 90° connector (elbow) with BSP female thread</p> 	<p>index</p>	<p>BSP female thread size</p>	<p>BSP female thread size</p>
	<p>AC-IBFF100-90</p>	<p>1"</p>	<p>1"</p>
<p>IBC T-piece with BSP male thread and 2 BSP female threads</p> 	<p>index</p>	<p>External thread size BSP</p>	<p>BSP female thread size</p>
	<p>AC-IBM200-2F200</p>	<p>2"</p>	<p>2 x 2"</p>
 <p>AC-IBP-BK AC-IBP-BK+ AC-IBF-D060-2X</p> <p>AC-IBT-F60-BK</p>	<p>index</p>	<p>description</p>	<p>colour</p>
	<p>AC-IBP-BK</p>	<p>spout without thread</p>	<p>black</p>
	<p>AC-IBP-W</p>	<p>spout without thread</p>	<p>white</p>
	<p>AC-IBT-F60-BK</p>	<p>faucet (tap) with female thread S60x6 with garden-type quick-connector plug</p>	<p>black</p>

NOTE: a two-part cap/cover must be used to install the spout (cap index: AC-IBF-D060-2X)