



**IBC connectors - covers / caps**


Vacuum valve (breather) with BSP or NPS male thread  	index	thread size	description
	AC-IBV-PV-M200	GZ 2" BSP	A valve designed for the unloading of IBC pallet containers allowing them to be unloaded without removing the lid. To be fitted on top of filler caps with a 2" threaded hole. Material: polypropylene. Spring: stainless steel. Seal: polyethylene (LDPE). Opening pressure: 0.069 bar (1 psi).
AC-IBV-PV-M200-NPS	GZ 2" NPS		

Coupling / valve cap with female thread DIN EN 12713  	index	female thread size DIN EN 12713
	AC-IBF-D060	S60x6
	AC-IBF-D060X	S60x6
	AC-IBF-D060-2X*	S60x6
	AC-IBF-D100	S100x8

\* - two-part cap, with removable cap in red; can be used to screw on the spout

IBC stopper with male thread DIN EN 12713  	index	External thread size DIN EN 12713
	AC-IBM-D060	S60x6

**IBC couplings - seals**

IBC coupling gasket with DIN EN 12713 thread  	index	Internal thread size DIN EN 12713	material type
	AC-IBU-060-LDPE	S60x6	polyethylene (LDPE)
	AC-IBU-060-PTFE	S60x6	PTFE
	AC-IBU-060-SANT	S60x6	SANTOPREN
	AC-IBU-060-VIT	S60x6	viton
	AC-IBU-060-VIT-O	S60x6	viton, o-ring (black)
	AC-IBU-060F-EPDM	S60x6	EPDM Food
	AC-IBU-092-SANT	S92x4	SANTOPREN
	AC-IBU-100-PTFE	S100x8	PTFE
	AC-IBU-100-SANT	S100x8	SANTOPREN
	AC-IBU-100-VIT	S100x8	viton

PLEASE NOTE: the above gaskets are intended for the "premium" version connectors. They are not intended for connectors in the economy version.