


# INDUSTRIAL FITTINGS - quick release couplings

## AKBO SS DN11.8 - couplings for water



**Material:** AISI 303/304L, balls - AISI 316  
**Working press.:** Up to 200 bar  
**Sealing:** Viton  
**Working temp.:** Up to +100°C

Full flow quick release couplings intended to connect water spray guns with hoses, lances and other accessories. BSP thread connection. Rubber socket protectors are optionally available to secure the coupling against damage if it falls on the floor.

picture	code	connection size	flow DN [mm]	spanner size [mm]	length [mm]	description
	AK-COUPPL-06-M	3/8"	10	30	49.5	Socket with male thread.
	AK-COUPPL-08-M	1/2"	11.8	30	49.5	
	AK-COUPPL-04-F	1/4"	11.8	30	44	Socket with female thread.
	AK-COUPPL-06-F	3/8"	11.8	30	44	
	AK-COUPPL-08-F	1/2"	11.8	30	44	
	AK-COUPPL-12-F	3/4"	11.8	32	44	
	AK-ADAPT-06-M	3/8"	10.4	22	39	Plug with male thread.
	AK-ADAPT-08-M	1/2"	11.8	22	39.8	
	AK-ADAPN-04-M	1/4"	8	16	42	Plug with male thread and two flat sides to fit a spanner.
	AK-ADAPT-04-F	1/4"	11.8	22	40.3	Plug with female thread.
	AK-ADAPT-08-F	1/2"	11.8	27	49.3	
	AK-ADAPW-11,5	D=11.5	11.5	-	30	Plug for welding.
	AK-ADAPN-06-F	3/8"	11.5	19	42	Plug with female thread and two flat sides to fit a spanner.
	AK-ADAPN-08-F	1/2"	11.5	22	42	
	AK-ADAPN-04-F	1/4"	11.5	17	55.2	Long plug with female thread and two flat sides to fit a spanner.
	AK-ADAPN-04-F-S	1/4"	11.5	17	40.3	Short plug with female thread and two flat sides to fit a spanner.
	AK-ADAPH13	12.8/13.3	10	no flange	57.5	Plug with hose tail 1/2".
	AK-ADAPH16-C21	15.8/16.8	10	flange 21	64	Plug with hose tail 5/8".
	AK-ADAPH19-C24	19.1/19.9	10	flange 24	65.2	Plug with hose tail 3/4".
	AK-COPROT1-BL	blue EPDM rubber				Socket protector.
	AK-COPROT1-BK	black EPDM rubber				
	AK-COPROT1-Y	yellow EPDM rubber				
	AK-COPRON2-BL	blue polyamide (nylon)				