Gun for use in explosive atmospheres (ATEX)

drawing	index	connection (inlet)	description
	AK-RNP01-BK-EX	GW 1/2" BSP	**AKBO HEAVY DUTY water gun for use in explosive atmosphere zones 1 and 2 (ATEX)**. TÜV certified. Made of AISI 316 stainless steel (trigger, bail: AISI 304), black EPDM rubber guards with resistance R<10^6 Ω, Viton seals (FDA). Adjustable outlet nozzle, infinitely variable flow control and a trigger lock. The trigger guard bail protects against uncontrolled opening of the water jet and against damage. Working pressure: 24 bar Max. working temp.: +60ºC Weight: approx. 0.97 kg Flow: 30 l/min (5 bar), 74 l/min (24 bar) *Spare parts: top guard and handle guard – available on special order.*

Lightweight plastic water gun

drawing	index	connection (inlet)	description
	AK-NN001-BL	GW 1/2" BSP	**Very lightweight AKBO plastic water gun**. Made of glass-fibre reinforced PA66 polyamide (FDA), AISI 304 stainless steel valve and lever, blue EPDM rubber guard, EPDM and Viton seals (FDA). Features an adjustable nozzle, infinitely variable flow control and a trigger lock. Used for washing in the food industry. Working pressure: 12 bar Max. working temp.: +50ºC Weight: approx. 0.5 kg Flow: 30 l/min (5 bar), 50 l/min (12 bar)

Water gun with rear trigger

drawing	index	version	connection (inlet)	description
	AK-RBT01-BL-U	standard, blue	GW 1/2" NPT	**AKBO stainless steel water gun with rear trigger.** Made of AISI 316 steel (trigger – AISI 304). Blue EPDM rubber guards, Viton seal (FDA). Features an adjustable outlet nozzle, infinitely variable flow control and a trigger lock. Max. working pressure: 24 bar Max. working temp.: +95ºC Weight: approx. 0.9 kg Flow: 28 l/min (5 bar), 58 l/min (15 bar) High-flow version: 48 l/min (5 bar), 90 l/min (15 bar)
	AK-RBTB1-BL-U	high-flow version (BIG FLOW), blue		

Guards and repair kits – see the "AKBO water guns – spare parts" section in this chapter.

BABY water gun

drawing		index	version	connection (inlet)	description
 AK-BABTN01-BL	 AK-BABTLF1-BK	AK-BABTN01-BL	standard, blue	GW 1/2" BSP	**Small, lightweight AKBO BABY aluminium water gun with rear trigger**. EPDM rubber covers and gaskets (FDA), AISI 304 stainless steel trigger lever. Features flow control. Black version with a 1/2" BSP male thread outlet for e.g. lance mounting. Max. working pressure: 12 bar Max. working temp.: +50ºC Weight: approx. 0.36 kg Flow: 18 l/min (5 bar), 24.5 l/min (12 bar) Brass and stainless steel versions also available on special order.
		AK-BABTLF1-BK	outlet GW 1/2" BSP, black		