AKBO spray nozzles and lances for guns and valves (2)

Guards for 1/4” spray nozzles

Nylon guard. 1/4” spray nozzle guard, material: polyamide (nylon), fitted between nozzle and lance - prevents loss of the guard.

stopper	blue	red	yellow	green	black	white	grey
index	AK-NOPRON-04-BL	AK-NOPRON-04-R	AK-NOPRON-04-Y	AK-NOPRON-04-G	AK-NOPRON-04-BK	AK-NOPRON-04-W	AK-NOPRON-04-GY
drawing							

Rubber guard. 1/4” spray nozzle guard, material: EPDM rubber, fitting: slid onto the nozzle – allows easy guard replacement.

stopper	blue	red	yellow	green	black
index	AK-NOPROT-04-BL	AK-NOPROT-04-R	AK-NOPROT-04-Y	AK-NOPROT-04-G	AK-NOPROT-04-BK
drawing					

Highlighted indices – most commonly used

1/4” spray lances

drawing	index	stopper insulation	length [cm]	description
	AK-LACX02XXX	-	25	**Straight lance.** 2 x 1/4” BSP male thread, working pressure up to 400 bar, temperature up to +150°C, AISI 304 stainless steel.
	AK-LACX06XXX	-	60	
	AK-LACX09XXX	-	90	
	AK-LACX12XXX	-	120	
	AK-LABX02XXX	-	25	**Bent lance.** 2 x 1/4” BSP male thread, bent at 15°, working pressure up to 400 bar, temperature up to +150°C, stainless steel AISI 304.
	AK-LABX05XXX	-	50	
	AK-LABX07XXX	-	70	
	AK-LABX09XXX	-	90	
	AK-LACB05XXX	blue	50	**Straight insulated lance.** 2 x 1/4” BSP male thread, working pressure up to 400 bar, temperature up to +150°C, AISI 304 stainless steel and plastic.
	AK-LACP07XXX	black	70	
	AK-LACP09XXX	black	90	
	AK-LACP12XXX	black	120	
	AK-LABP07XXX	black	70	**Bent insulated lance.** 2 x 1/4” BSP male thread, bent at 15°, working pressure up to 400 bar, temperature up to +150°C, stainless steel AISI 304 and plastic.
	AK-LACX02ASPB2530	-	25	**Straight lance with guarded nozzle and quick coupling.** Lance with 2530 spray nozzle (25°, 30 l/min - 20 bar, 1/4” BSPT male thread) in a blue rubber guard, with DN11,8 quick coupling plug*, stainless steel.
	AK-LACX05ASPB2530	-	50	
	AK-LACX06RSPB1530	-	60	**Straight lance with guarded nozzle and adaptor.** Lance with 1530 spray nozzle (15°, 30 l/min - 20 bar, 1/4” BSPT male thread) in a blue rubber guard, with adaptor with 1/2” BSP female thread, stainless steel.

Other assembly combinations of lance type and length, nozzle types, guard types and colours available in these configurations.

1/4” spray nozzles with quick coupling

drawing	index	nozzle used	description
	AK-ADASN-04-2530-BL	2530 spray nozzle (25°, 30 l/min - 20 bar, GZ 1/4” BSPT) in a blue rubber guard	**Guarded nozzle with short DN11,8 quick coupling plug*** (plug index: AK-ADAPN-04-F-S, stainless steel).
	AK-ADASN-04-2560-Y	2560 spray nozzle (25°, 60 l/min - 20 bar, GZ 1/4” BSPT) in a yellow rubber guard	
	AK-ADAPN-04-2530-BL	2530 spray nozzle (25°, 30 l/min - 20 bar, GZ 1/4” BSPT) in a blue rubber guard	**Guarded nozzle with long DN11,8 quick coupling plug*** (plug index: AK-ADAPN-04-F, stainless steel).

** - DN11,8 quick couplings – see INDUSTRIAL FITTINGS section, chapter “Stainless steel quick couplings for water”*

Other assembly combinations of nozzle types and guard colours available in these configurations.