



CLEANING AND WASHING - low pressure

Foaming, washdown and detergent dispensing devices

Multifunctional AKBO guns to mount lances and nozzles




Foaming and spraying lances and nozzles extend the range of water spray gun applications. Lances and nozzles can be easily changed, thus adapting the gun to other functions. AKBO water spray guns in this version have 1/2" BSP male thread connection on the outlet or DN11.8 quick release socket in rubber protector, thus making the replacement of nozzles very easy.

picture	code	version	description
	AK-KLML001-BL	brass, no trigger insulation, blue	Water spray gun with 1/2" BSP male thread connector to mount a lance. Smooth flow control, and trigger lock. Stainless steel trigger, EPDM rubber cover, EPDM seals (FDA, DVGW) or Viton (AK-RLCP1- BL, FDA). Connection: 1/2" BSP female thread. Max. working press.: 24 bar. Max. working temp.: +95°C. Weight: about 0,84 kg. Flow rate: 30 l/min (5 bar), 75 l/min (24 bar).
	AK-CL001-BL	chromium-plated brass, insulated trigger, blue	
	AK-RL001-BL	AISI 316 stainless steel, insulated trigger, blue	
	AK-KLMCP1-BL	brass, no trigger insulation, blue	Foam, spray and disinfection gun with DN 11.8* quick release socket on the outlet to mount a lance. Smooth flow control, and trigger lock. Stainless steel trigger, EPDM rubber cover, EPDM seals (FDA, DVGW) or Viton (AK-RLCP1- BL, FDA). Connection: 1/2" BSP female thread. Max. working press.: 24 bar. Max. working temp.: +95°C. Weight: about 0,9 kg. Increased flow rate for better foam quality, automatic flow shut-off when the trigger is released.
	AK-CLCP1-BL	chromium-plated brass, insulated trigger, blue	
	AK-RLCP1-BL	stainless steel, insulated trigger, blue	

* - AKBO DN11.8 quick release couplings - see section „INDUSTRIAL FITTINGS - quick release couplings”

Lightweight foam gun

picture	code	version	description
	AK-NLFW2	polyamide, no trigger insulation, blue	Lightweight foaming and washdown gun made of glass fibre reinforced polyamide. Complete with a flat foam nozzle. Stainless steel trigger, spring and stem of the valve, EPDM and Viton sealing. EPDM rubber cover. Connection: 1/2" BSP female thread. Max. working press.: 12 bar. Max. working temp.: +50°C. Weight: about 0,66 kg.