AKBO multifunction gun (1)



The AKBO multifunction gun is fitted with a special DN11,8 quick coupling plug at the outlet (in the MNAP2-BL version with a stainless steel bow-type guard). Using this gun you can:
- apply foam to the surfaces being cleaned (gun with foam nozzle, or lance, fed with an aqueous solution of cleaning and foaming agent);
- apply foam to the surfaces being cleaned (gun with tank for cleaning and foaming agent, fed with water);
- rinse with water in an adjustable jet from the gun – without fitting additional accessories;
- spray (e.g. with disinfectant) (gun with lance with spray nozzle fed with an aqueous solution of disinfectant).

Gun used for washing and rinsing surfaces in the food industry, in kitchens, fish and meat processing plants.
Note: Quick couplings for this gun and nozzles are not interchangeable with other systems.

drawing	index	material	connection (inlet)	description
	AK-MNA02-BL	brass	GW 1/2” BSP	**Multifunction AKBO gun, fitted with a DN11.8 quick-coupling plug with a special profile at the outlet.** Trigger, spring and valve stem in stainless steel AISI 304, EPDM seals (FDA). Guards of blue EPDM rubber. Version AK-MNAP2-BL fitted with an outlet guard in the form of a stainless steel bail. Various types of nozzles, lances, a foam generator can be connected to it, or it can be used without additional accessories. Max. working pressure: 24 bar (for AK-NNA02-BL: 12 bar) Max. working temperature: +95°C (for AK-NNA02-BL: +50°C) Weight: approx. 0.9 kg (for AK-NNA02-BL: 0.55 kg)
	AK-MNAP2-BL	brass		
	AK-NNA02-BL	glass fibre reinforced polyamide PA66		

Nozzles for the multifunction AKBO gun

drawing	index	description
	AK-LANFC01	**Standard nylon foam nozzle**, with quick-coupling socket DN11.8 of chromed brass.
	AK-LANFRC1	**Standard nylon foam nozzle**, with quick-coupling socket DN11,8 in stainless steel.
	AK-LANFC02	**Flat foam nozzle of nylon**, with quick-coupling socket DN11.8 of chromed brass.