












AKBO HEAVY DUTY sprayers

Industrial water nozzles with handle with head adjustable by rotation (from completely closed through narrow to wide spray). Head made of brass or AISI 303 stainless steel, seals made of EPDM (FDA), head cover made of high-strength polyoxymethylene (POM). Handle in brass or AISI 316 stainless steel, covered with EPDM rubber. Versions without handle (heads only) are also available, which can be mounted directly to the hose with the appropriate nozzle. Operating pressure up to 16 bar, operating temperature up to +80°C. Flow rate: 110 l/min (5 bar), 150 l/min (16 bar). Weight (head + handle) - approx. 0.5 kg. Used for cleaning in the food industry, meat and fish plants, breweries and beverage factories, industrial kitchens and dairies.

drawing	index	material	connection	colour head	colour handle		
 AK-MSH03-BL AK-MSHH4-BK	AK-MSH03-BL	brass	GW 1/2" BSP	black	blue		
	AK-MSH03-R			black	red		
	AK-MSH03-W			black	white		
	 AK-MSHH4-BK		AK-MSHH4-BK	PG 1/2" BSP	black	-	
 AK-GRIPM01-BL AK-GRIPM01-R AK-GRIPM01-W			AK-GRIPM01-BL	2xGW 1/2" BSP	-	blue	
			AK-GRIPM01-R		-	red	
	AK-GRIPM01-W		-		white		
 AK-RSH03-BL AK-RSH03-R AK-RSH03-W AK-RSHW3-W AK-RSHH4-BK AK-RSHH4-W	AK-RSH03-BL		stainless steel	GW 1/2" BSP	black	blue	
	AK-RSH03-R				black	red	
	AK-RSH03-W				black	white	
	 AK-RSHW3-W			AK-RSHW3-W	PG 1/2" BSP	white	white
				AK-RSHH4-BK		black	-
		AK-RSHH4-W		white		-	
 AK-GRIPR01-BL AK-GRIPR01-R AK-GRIPR01-W	AK-GRIPR01-BL	2xGW 1/2" BSP		-	blue		
	AK-GRIPR01-R			-	red		
	AK-GRIPR01-W			-	white		

AKBO TWISTER nozzles

High-flow, powerful water jet nozzle at low supply pressure. The head is made of stainless steel (AISI 304), the head ring of EPDM, the cover of high-strength acetal (POM). Ideal for cleaning large areas in a short time. Suitable for cleaning: tanks, yards, ships, trucks, etc. Thanks to the rotating head, the width of the spray can be accurately adjusted and the opening and closing of the water jet can be adjusted. Can be fitted directly to a hose with the appropriate nozzle. Operating pressure up to 16 bar. Operating temperature: +60°C. Weight, depending on version: 0.345 ÷ 0.8 kg.

drawing	index	connection (inlet)	flow	length [mm]	outside diameter of head [mm]
	AK-TWRWR01XL	1" BSP THREADED SOCKET (60° cone)	300 l/min (4 bar), 500 l/min (16 bar)	120	79
	AK-TWRWR02L	GZ 3/4" BSP (60° cone)	140 l/min (4 bar), 220 l/min (16 bar)	116	63
	AK-TWRWR02M	PG 1/2" BSP (60° cone)	100 l/min (4 bar), 160 l/min (16 bar)	113	55

