



INDUSTRIAL FITTINGS - fittings, connectors

Fittings - AK type

picture	code	thread size [BSP]	flange size [mm]	hose I.D. [inch]	flow diameter [mm]	description
	AK-RVST13-C17-SP	1/2	17	1/2	10	Fitting with BSP male thread with 200 mm hose protection spring. Material: stainless steel. Working press.: up to 40 bar.
	AK-RVST13-C20-SP	1/2	20	1/2	10	
	AK-RVST16-C21-SP	1/2	21	5/8	13	
	AK-RVST19-C24-SP	1/2	24	3/4	14	

picture	code	thread size [BSPT]	flange size [mm]	hose I.D. [inch]	flow diameter [mm]	description
	AK-SWIFB13-C17	1/2	17	1/2	10	Swivel fitting with NPT male thread. Material: stainless steel. Working press.: up to 40 bar. * - with 200 mm hose protection spring.
	AK-SWIFB13-C20	1/2	20	1/2	10	
	AK-SWIFB13-C20-SP*	1/2	20	1/2	10	
	AK-SWIFB16-C21	1/2	21	5/8	13	
	AK-SWIFB16-C21SP*	1/2	21	5/8	13	
	AK-SWIFB19-C24	1/2	24	3/4	14	
	AK-SWIFB19-C24SP*	1/2	24	3/4	14	

picture	code	female thread size	male thread size	flow diameter [mm]	material	description
	AK-SWM-09-08	1/2"	1/2"	9	brass	Swivel fitting with BSP female and BSP male thread. Working press.: up to 30 bar. Seal: - EPDM for brass - Viton for stainless steel
	AK-SWM-09-12	3/4"	1/2"	9		
	AK-SWM-12-12	3/4"	3/4"	12		
	AK-SWM-14-12-08	3/4"	1/2"	14		
	AK-SWM-18-16	1"	1"	18		
	AK-SWR-09-08	1/2"	1/2"	9	stainless steel	
	AK-SWR-09-12-08	3/4"	1/2"	9		
	AK-SWR-12-12	3/4"	3/4"	12		
	AK-SWR-14-12-08	3/4"	1/2"	14		
	AK-SWR-18-16	1"	1"	18		
	AK-SWC-09-08	1/2"	1/2"	9	brass chromium	
	AK-SWC-09-12-08	3/4"	1/2"	9		
AK-SWC-14-12-08	3/4"	1/2"	14			