



AirTac G Series



GFR filter-regulator

Size: 200, 300, 400, 600
Output pressure range: 0÷9 bar
Degree of filtration: 40 µm
Supply pressure: Up to 10 bar
Operating temp: Up to +70°C
Connection: GW BSP 1/8" ÷ 1"
Condensate drain: Automatic (A) **Flow rate:**
 2100 l/min - 200
 3800 l/min - 300
 6750 l/min - 400
 11100 l/min - 600
 (at 6 bar ve. pressure and Δp= 1 bar)

200	300	400	600	Connection
AT-GFR200-06				1/8"
AT-GFR200-08	AT-GFR300-08			1/4"
	AT-GFR300-10	AT-GFR400-10		3/8"
	AT-GFR300-15	AT-GFR400-15		1/2"
			AT-GFR600-20	3/4"
			AT-GFR600-25	1"

Mounting bracket and pressure gauge included.



GL lubricator

Size: 200, 300, 400, 600
Tank capacity:
 25 cm³ - 200 series
 75 cm³ - 300 series
 160 cc - 400 series
 380 cc - 600 series
Supply pressure: Up to 10 bar
Operating temp: Up to +70°C
Connection: GW BSP 1/8"÷ 1"
Flow rate:
 3200 l/min - 200
 5400 l/min - 300
 8300 l/min - 400
 12000 l/min - 600
 (at 6 bar ve. pressure and Δp= 1 bar)

200	300	400	600	Connection
AT-GL200-06				1/8"
AT-GL200-08	AT-GL300-08			1/4"
	AT-GL300-10	AT-GL400-10		3/8"
	AT-GL300-15	AT-GL400-15		1/2"
			AT-GL600-20	3/4"
			AT-GL600-25	1"

Mounting bracket included.

