



AirTac G-Series



Mini SDR reducer

Size: 100, 200
Output pressure range: 0÷9 bar
Supply pressure: Up to 10 bar
Operating temp: Up to +70°C
Connection: GW BSP M5"÷ 1/4"
Flow rate: 150 l/min - 100
 500 l/min - 200
 (at an actuating pressure of 6 bar and Δp= 1 bar)

100	200	Connection
AT-SDR100-M5		M5
AT-SDR100-06	AT-SDR200-06	1/8"
	AT-SDR200-08	1/4"

Mounting bracket and pressure gauge included.



GR reducer

Size: 200, 300, 400, 600
Output pressure range: 0÷9 bar
Supply pressure: Up to 10 bar
Operating temp: Up to +70°C
Connection: GW BSP 1/8"÷ 1"
Flow rate: 3000 l/min - 200
 4000 l/min - 300
 7500 l/min - 400
 12000 l/min - 600
 (at an actuating pressure of 6 bar and Δp= 1 bar)

200	300	400	600	Connection
AT-GR200-06				1/8"
AT-GR200-08	AT-GR300-08			1/4"
	AT-GR300-10	AT-GR400-10		3/8"
	AT-GR300-15	AT-GR400-15		1/2"
			AT-GR600-20	3/4"
			AT-GR600-25	1"

Mounting bracket and pressure gauge included.

