The Band-It banding system®

Tools for fitting Standard / Giant and Junior bands

drawing	index	permitted band width [inch]	application	description
	BD-C07599	1/4” ÷ 3/4”	Band-It® Standard 1/4” ÷ 3/4”	Band tensioner (ratchet) made of corrosion-resistant galvanised steel, with plastic parts, with a built-in blade for cutting the band. Ideal for confined spaces. Maximum band thickness 0.63 mm
	BD-C00189	1/4” ÷ 3/4”	Band-It® Standard 1/4” ÷ 3/4” Band-It® Junior – tool used only with adaptor BD-J00199	Band tensioner (tensioner) screw-type with a built-in blade for cutting the band. Maximum band band 0.38 ÷ 0,76 mm
	BD-J00199	1/4” ÷ 3/4”	Band-It® Junior	Adaptor pre-forming clamps, used with tool DB-C00189
	BD-C00399	1/4” ÷ 3/4”	Band-It® Standard Band-It® Standard Giant 3/4”	Stronger version of the band tensioner BD-C00189, intended mainly for materials 1.1 mm thick and 3/4” wide. Not recommended for thinner bands of 0.38 mm or 0.51 mm. For use when greater tensioning force is required (heavy duty)
	BD-G40299	3/4” ÷ 1.1/4”	Band-It® Standard Giant	Band tensioner (tensioner) screw-type with a built-in blade for cutting the band. Intended for bands 1.1 mm thick.