

INDUSTRIAL FITTINGS - clips, clamps, ferrules

Band-It® banding assembly system



Band-It® Ultra-Lok®

The most robust of all banding systems intended for the most requiring applications. The banding is available as preformed, double wrap clamps with built-in buckles or as band in pieces that allow making a clamp directly on the hose (in a single or double wrap). A double wrap is recommended for superior strength. The smooth band properly mounted on a smooth, uncorrugated hose ensures tight connection of a fitting which reduces leaks paths into a clamp itself. Assembly with BD-UL9010 or BD-UL4000B electric tools.

picture	code (AISI 201)	band width * [inch]	band thickness [mm]	maximum diameter wrap [mm]	package [pcs]
Band (a double wrap clamp with a built-in buckle) 	BD-UL2799	1/2	0.76	38	100
	BD-UL2839			50	100
	BD-UL2869			69	100
	BD-UL2919			101	100
	BD-UL2279	3/4		50	100
	BD-UL2109			69	50
	BD-UL2119			76	50
	BD-UL2129			88	50
	BD-UL2139			101	25
	BD-UL2149			114	25
	BD-UL2159			127	25
	BD-UL2709			139	25
	BD-UL2169			152	25
	BD-UL2179			165	25
	BD-UL2189			177	25
	BD-UL2199			203	25
	BD-UL2289			228	10

picture	code (AISI 201)	band width * [inch]	band length [mm]	maximum diameter wrap [mm]		package [pcs]
				single	double	
Straight bands 	BD-UL1018	1/2	457	76	-	50
	BD-UL1024		610	127	64	50
	BD-UL1028		711	152	76	50
	BD-UL1032		813	178	89	50
	BD-UL1036		914	203	102	50
	BD-UL1046		1168	279	140	25
	BD-UL1056		1422	356	178	25
	BD-UL1070		1778	457	229	25
	BD-UL1086		2184	559	280	25
	BD-UL1096		2438	635	318	25
	BD-UL1106		2692	711	356	25
	BD-UL1116		2946	787	394	25

* - Use BD- M09387 shear plate to adjust the tool before forming 1/2" clamp.