


INDUSTRIAL FITTINGS - quick release couplings










CEJN couplings



320 series DN 7.6

Material: Body - brass / zinc-plated steel
 Ferrule, plug - hardened zinc-plated steel
 Valve: brass
 Spring and balls: stainless steel,
Flow rate: 2100 l/min (Pe = 6 bar, Δp=0.5 bar)
 2250 l/min - ESAFE (Pe = 6 bar, Δp=0.5 bar)
Working press.: 16 bar (safety factor 8.75)
Working temp.: From -20°C up to +100°C (NBR)

A single shut-off quick release coupling for general purpose application in industry, mainly in pneumatic systems. For one hand operation with minimum coupling force. Manufactured according to Eurostandard 7.6. Available socket versions: STANDARD, ESAFE (vented safety version, vented before disconnection to avoid the risk of sudden separation, complies with ISO 4414 and EN 983 standard), SOFT-LINE (in soft housing, to protect quick release coupling from mechanical impact), MULTI-LINK (for modular connection systems).

picture	code	connection	picture	code	connection
	CJ-103202002	6.3 mm		CJ-103205001	5 mm
	CJ-103202003	8 mm		CJ-103205002	6.3 mm
	CJ-103202009	9 mm		CJ-103205003	8 mm
	CJ-103202004	10 mm		CJ-103205009	9 mm
	CJ-103202005	13 mm		CJ-103205004	10 mm
	CJ-103201932	6.3 mm		CJ-103205005	13 mm
	CJ-103201934	10 mm		CJ-103205151	1/8" BSPT male
	CJ-103201935	13 mm		CJ-103205152	1/4" BSPT male
	CJ-103202152	1/4" BSPT male		CJ-103205154	3/8" BSPT male
	CJ-103202154	3/8" BSPT male		CJ-103205155	1/2" BSPT male
	CJ-103202155	1/2" BSPT male	CJ-103205263	1/4" BSP male	
	CJ-103202202	1/4" BSP female		CJ-103205264	3/8" BSP male
	CJ-103202204	3/8" BSP female		CJ-103205265	1/2" BSP male
	CJ-103202205	1/2" BSP female		CJ-103205451	1/8" NPT male
	CJ-103201086	10 mm		CJ-103205452	1/4" NPT male
	CJ-103201087	13 mm		CJ-103205454	3/8" NPT male
	CJ-103201246	1/4" BSP female		CJ-103205455	1/2" NPT male
	CJ-103201247	3/8" BSP female		CJ-103205201	1/8" BSP female
	CJ-103201942	1/4" BSP female		CJ-103205202	1/4" BSP female
				CJ-103205204	3/8" BSP female
				CJ-103205205	1/2" BSP female
			CJ-103205401	1/8" NPT female	
			CJ-103205402	1/4" NPT female	
			CJ-103205404	3/8" NPT female	
			CJ-103205405	1/2" NPT female	