


# INDUSTRIAL FITTINGS - quick release couplings

## CEJN couplings



### 410 series DN 10.4

**Material:** Body - brass / zinc-plated steel  
 Ferrule, plug - hardened zinc-plated steel  
 Valve: brass

**Flow rate:** Spring and balls: stainless steel,  
 3900 l/min (Pe = 6 bar, Δp=0.5 bar)  
 4000 l/min - ESAFE (Pe = 6 bar, Δp=0.5 bar)

**Working press.:** 16 bar (safety factor 8.75)  
**Working temp.:** From -20°C up to +100°C (NBR)

A single shut-off quick release coupling for general purpose application in industry, mainly in pneumatic systems. For one hand operation with minimum coupling force. Manufactured according to Eurostandard 10.4. Available socket versions: STANDARD and ESAFE (vented safety version, vented before disconnection to avoid the risk of sudden separation, complies with ISO 4414 and EN 983 standard).

picture	code	connection	picture	code	connection
	CJ-104102003	8 mm		CJ-104105002	6.3 mm
	CJ-104102004	10 mm		CJ-104105003	8 mm
	CJ-104102005	13 mm		CJ-104105004	10 mm
	CJ-104102006	16 mm		CJ-104105005	13 mm
	CJ-104102007	19 mm		CJ-104105006	16 mm
	CJ-104102154	3/8" BSPT male		CJ-104105007	19 mm
	CJ-104102155	1/2" BSPT male		CJ-104105152	1/4" BSPT male
	CJ-104102157	3/4" BSPT male	CJ-104105154	3/8" BSPT male	
	CJ-104102204	3/8" BSP female	CJ-104105155	1/2" BSPT male	
	CJ-104102205	1/2" BSP female	CJ-104105157	3/4" BSPT male	
	CJ-104102207	3/4" BSP female	CJ-104105454	3/8" NPT male	
			CJ-104105455	1/2" NPT male	
			CJ-104105457	3/4" NPT male	
			CJ-104105202	1/4" BSP female	
			CJ-104105204	3/8" BSP female	
			CJ-104105205	1/2" BSP female	
			CJ-104105207	3/4" BSP female	
			CJ-104105404	3/8" NPT female	
			CJ-104105405	1/2" NPT female	
		CJ-104105407	3/4" NPT female		