













HIGH PRESSURE - UHP equipment

Connectors

Adapters enable connection of quick release couplings with Ultra High Pressure (UHP) hoses as well as connection of the assemblies with UHP porting blocks. Made of black zinc-plated steel.

picture	code	A1 thread	seal	A2 thread	seal	L [mm]	span. [mm]	press. [bar]
	CJ-HP-199501622	BSP 1/4"	60° inner cone	BSP 1/4"	60° inner cone	31.5	21	2500
	CJ-HP-199501623	BSP 1/4"	60° inner cone	NPT 1/4"	on thread	32	21	1500
	CJ-HP-199501621	BSP 1/4"	60° inner cone	BSPT 1/4"	on thread	33	21	
	CJ-HP-199501603	BSP 1/4"	60° inner cone	NPT 3/8"	on thread	34	21	
	CJ-HP-199501604	BSP 1/4"	60° inner cone	BSPT 3/8"	on thread	35	21	
	CJ-HP-199501602	BSP 1/4"	60° inner cone	BSP 1/4"	120° outer cone	39	21	
	CJ-HP-199501605	BSP 1/4"	60° inner cone	UNF 9/16"-18	60° outer cone	37	17	2500
	CJ-HP-199501606	BSP 1/4"	60° inner cone	UNF 3/4"-16	60° outer cone	42	21	
	CJ-HP-199501607	BSP 1/4"	60° inner cone	M16x1.5	60° outer cone	37	19	
	CJ-HP-199501608	BSP 1/4"	60° inner cone	M22x1.5	60° outer cone	48	27	
	CJ-HP-199500028	BSP 1/4"	120° outer cone	M14x1.5	60° inner cone	37.5	17	
	CJ-HP-199500029	BSP 1/4"	120° outer cone	UNF 9/16"-18	60° inner cone	37.5	17	