CEJN quick couplings – NON DRIP (2)

series	description	index	DN [mm]	connection	material body	material seals	L [mm]	D [mm]	SW [mm]
567	plug without valve	CJ-ND-105675200	9	GW 1/2" BSP	nickel-plated brass	NBR	56,5	29	27
	plug with valve	CJ-ND-105676200	9	GW 1/2" BSP	nickel-plated brass	NBR	56,5	29	27
	plug with valve	CJ-ND-105676210	9	GW 1/2" BSP	nickel-plated brass	viton (FPM)	56,5	29	27
	plug with valve	CJ-ND-105676220	9	GW 1/2" BSP	nickel-plated brass	EPDM	56,5	29	27
667	socket without valve	CJ-ND-106670200	14	GW 3/4" BSP	nickel-plated brass	NBR	74,2	41	36
	socket with valve	CJ-ND-106671200	14	GW 3/4" BSP	nickel-plated brass	NBR	74,2	41	36
	socket with valve	CJ-ND-106671210	14	GW 3/4" BSP	nickel-plated brass	viton (FPM)	74,2	41	36
	socket with valve	CJ-ND-106671220	14	GW 3/4" BSP	nickel-plated brass	EPDM	74,2	41	36
	plug without valve	CJ-ND-106675200	14	GW 3/4" BSP	nickel-plated brass	NBR	66	36	34
	plug with valve	CJ-ND-106676200	14	GW 3/4" BSP	nickel-plated brass	NBR	66	36	34
	plug with valve	CJ-ND-106676210	14	GW 3/4" BSP	nickel-plated brass	viton (FPM)	66	36	34
	plug with valve	CJ-ND-106676220	14	GW 3/4" BSP	nickel-plated brass	EPDM	66	36	34
767	socket without valve	CJ-ND-107670200	19	GW 1" BSP	nickel-plated brass	NBR	82	52	46
	socket with valve	CJ-ND-107671200	19	GW 1" BSP	nickel-plated brass	NBR	82	52	46
	socket with valve	CJ-ND-107671210	19	GW 1" BSP	nickel-plated brass	viton (FPM)	82	52	46
	socket with valve	CJ-ND-107671220	19	GW 1" BSP	nickel-plated brass	EPDM	82	52	46
	plug without valve	CJ-ND-107675200	19	GW 1" BSP	nickel-plated brass	NBR	67,5	44	41
	plug with valve	CJ-ND-107676200	19	GW 1" BSP	nickel-plated brass	NBR	67,5	44	41
	plug with valve	CJ-ND-107676210	19	GW 1" BSP	nickel-plated brass	viton (FPM)	67,5	44	41
	plug with valve	CJ-ND-107676220	19	GW 1" BSP	nickel-plated brass	EPDM	67,5	44	41
277	socket with valve	CJ-ND-102771210	4	GW 1/4" BSP	AISI 316	viton (FPM)	43,5	23	19
	plug with valve	CJ-ND-102776210	4	GW 1/4" BSP	AISI 316	viton (FPM)	48,5	20	19
477	socket with valve	CJ-ND-104771210	6	GW 3/8" BSP	AISI 316	viton (FPM)	45	29	22
	plug with valve	CJ-ND-104776210	6	GW 3/8" BSP	AISI 316	viton (FPM)	52	24	22
577	socket without valve	CJ-ND-105770210	9	GW 1/2" BSP	AISI 316	viton (FPM)	52,5	34	27
	socket with valve	CJ-ND-105771210	9	GW 1/2" BSP	AISI 316	viton (FPM)	52,5	34	27
	plug without valve	CJ-ND-105775210	9	GW 1/2" BSP	AISI 316	NBR	56,5	29	27
	plug with valve	CJ-ND-105776210	9	GW 1/2" BSP	AISI 316	viton (FPM)	56,5	29	27
677	socket without valve	CJ-ND-106770210	14	GW 3/4" BSP	AISI 316	viton (FPM)	74,2	41	36
	socket with valve	CJ-ND-106771210	14	GW 3/4" BSP	AISI 316	viton (FPM)	74,2	41	36
	plug without valve	CJ-ND-106775210	14	GW 3/4" BSP	AISI 316	NBR	66	39	36
	plug with valve	CJ-ND-106776210	14	GW 3/4" BSP	AISI 316	viton (FPM)	66	39	36
777	socket without valve	CJ-ND-107770210	19	GW 1" BSP	AISI 316	viton (FPM)	82	52	46
	socket with valve	CJ-ND-107771210	19	GW 1" BSP	AISI 316	viton (FPM)	82	52	46
	plug without valve	CJ-ND-107775210	19	GW 1" BSP	AISI 316	NBR	67,5	44	41
	plug with valve	CJ-ND-107776210	19	GW 1" BSP	AISI 316	viton (FPM)	67,5	44	41



DN [mm]	for series	index	
		coupler cap	adapter cap
4	267/277	CJ-ND-102671000	CJ-ND-102671050
6	467/477	CJ-ND-104671000	CJ-ND-104671050
9	567/577	CJ-ND-105671000	CJ-ND-105671050
14	667/677	CJ-ND-106671000	CJ-ND-106671050
19	767/777	CJ-ND-107671000	CJ-ND-107671050

version	DN 4	DN 6	DN 9	DN 14	DN 19
free-flow	32 l/min	62 l/min	187 l/min	413 l/min	803 l/min
single shut-off	17 l/min	36 l/min	78 l/min	193 l/min	334 l/min
double shut-off	17 l/min	36 l/min	76 l/min	168 l/min	306 l/min

Note: flow given for **Δt = 4 bar**