

INDUSTRIAL FITTINGS - clips, clamps, ferrules



CAW

Clamps designed to assemble lightweight PVC and rubber hoses. The smooth internal layer of the band protects the hose against damage. Assembly and disassembly is fast and easy when tools intended for the purpose are used. As made of AISI 304 (W4) stainless steel, it can be used in food, medical, electronic and automotive industry (air conditioning).

code	I.D. [mm]	min. / max. diameter range [mm]	band thickness [mm]	band width [mm]
CL-CAW-070	7.0	5.7 ÷ 7.0	0.5	5
CL-CAW-080	8.0	6.8 ÷ 8.0		
CL-CAW-087	8.7	7.0 ÷ 8.7		
CL-CAW-090	9.0	7.3 ÷ 9.0		
CL-CAW-095	9.5	7.8 ÷ 9.5		
CL-CAW-100	10.0	8.3 ÷ 10.0		
CL-CAW-105	10.5	8.8 ÷ 10.5		
CL-CAW-109	10.9	9.2 ÷ 10.9		
CL-CAW-113	11.3	9.6 ÷ 11.3		
CL-CAW-118	11.8	10.1 ÷ 11.8		
CL-CAW-119	11.9	9.4 ÷ 11.9		
CL-CAW-123	12.3	9.8 ÷ 12.3		
CL-CAW-128	12.8	10.3 ÷ 12.8		
CL-CAW-133	13.3	10.8 ÷ 13.3		
CL-CAW-138	13.8	11.3 ÷ 13.8		
CL-CAW-140	14.0	11.5 ÷ 14.0		
CL-CAW-142	14.2	11.7 ÷ 14.2		
CL-CAW-145	14.5	12.0 ÷ 14.5		
CL-CAW-148	14.8	12.3 ÷ 14.8		
CL-CAW-153	15.3	12.8 ÷ 15.3		
CL-CAW-157	15.7	13.2 ÷ 15.7		
CL-CAW-160	16.0	13.5 ÷ 16.0		
CL-CAW-162	16.2	13.7 ÷ 16.2		
CL-CAW-166	16.6	14.1 ÷ 16.6		
CL-CAW-168	16.8	14.3 ÷ 16.8		
CL-CAW-170	17.0	14.5 ÷ 17.0		
CL-CAW-175	17.5	15.0 ÷ 17.5		
CL-CAW-178	17.8	14.6 ÷ 17.8		
CL-CAW-180	18.0	14.8 ÷ 18.0		
CL-CAW-185	18.5	15.3 ÷ 18.5		

Tools for CAW clamps assembly

clamping pliers



CL-CLTEN1099

compact pneumatic pliers



CL-UTSV001