

# INDUSTRIAL FITTINGS - clips, clamps, ferrules



## DCL

DCL clamps are made of a one-piece band with a locking pawl which prevents accidental unlocking. Clamping force is evenly distributed on the pawl. The smooth internal layer of the band protects the hose against damage. Assembly and disassembly is fast and easy when tools intended for the purpose are used. As made of AISI 304 (W4) stainless steel, it can be used in food, home appliance and automotive industry. Colour-coded stripes on the clamps facilitate identification.

code	I.D. [mm]	min. / max. diameter range [mm]	band thickness [mm]	band width [mm]	color
CL-DCL-080	8.0	8.5 ÷ 9.5	0.5	6	blue
CL-DCL-085	8.5	9.0 ÷ 10.0			green
CL-DCL-090	9.0	9.5 ÷ 11.0			violet
CL-DCL-095	9.5	10.0 ÷ 11.5			black
CL-DCL-100	10.0	10.5 ÷ 11.5			green
CL-DCL-105	10.5	11.0 ÷ 12.0			blue
CL-DCL-110	11.0	11.5 ÷ 12.5			green
CL-DCL-115	11.5	12.0 ÷ 13.0			violet
CL-DCL-120	12.0	12.5 ÷ 13.5			black
CL-DCL-125	12.5	13.0 ÷ 14.0			red
CL-DCL-130	13.0	13.5 ÷ 14.5	0.6	8	green
CL-DCL-135	13.5	14.0 ÷ 15.0			violet
CL-DCL-140	14.0	14.5 ÷ 15.5			red
CL-DCL-145	14.5	15.0 ÷ 16.0			violet
CL-DCL-150	15.0	15.5 ÷ 16.5			black
CL-DCL-155	15.5	16.0 ÷ 17.0			blue
CL-DCL-160	16.5	16.5 ÷ 17.5			green
CL-DCL-165	17.0	17.0 ÷ 18.0			black
CL-DCL-170	17.5	17.5 ÷ 18.5			red
CL-DCL-175	18.0	18.0 ÷ 19.0			blue
CL-DCL-180	18.5	18.5 ÷ 19.5			green
CL-DCL-185	19.0	19.0 ÷ 20.0			violet
CL-DCL-190	19.5	19.5 ÷ 21.0			blue
CL-DCL-195	20.0	20.0 ÷ 21.5			black
CL-DCL-200	20.5	20.5 ÷ 22.0			red
CL-DCL-205	21.0	21.0 ÷ 22.5	blue		
CL-DCL-210	21.5	21.5 ÷ 23.0	green		
CL-DCL-215	22.0	22.0 ÷ 23.5	violet		
CL-DCL-220	22.5	22.5 ÷ 24.0	black		
CL-DCL-225	23.0	23.0 ÷ 24.5	red		
CL-DCL-230	23.5	23.5 ÷ 25.0	blue		
CL-DCL-235	24.0	24.0 ÷ 25.5	green		

### Tools for DCL clamps assembly

clamping pliers



CL-CLICUT5201

compact pneumatic pliers



CL-UTSV001