

INDUSTRIAL HOSES - steam

Fittings for steam hoses



SBC clamp for MS, GF fittings

Material: Malleable iron, stainless steel, brass

Clamp designed to assemble MS and GF fittings on a hose.

Minimum and maximum diameters listed in the table, are only an indication for a clamp choice. Structure of the hose may vary so it is essential to check if the actual size of a clamp matches. Clamps should be regularly checked and tightened during operation.

code (malleable iron)	code (stainless steel)	code (brass)	hose I.D. [inch]	hose O.D. [mm]		number of bolts
				min.	max.	
DX-SBC2-04-14-17	-	-	1/4	14	17	2
DX-SBC2-06-17-22	-	-	3/8	17.5	22	
DX-SBC2-08-20-24	-	-	1/2	20.5	24	
DX-SBC2-08-24-27	DX-SBC2-08-24/27-SS	DX-SBC2-08-24/27-B	1/2	24	27	
DX-SBC2-12-27-30	-	-	1/2	27	30	
DX-SBC2-12-30-33	DX-SBC2-12-30/33-SS	DX-SBC2-12-30/33-B	3/4	30	33	
DX-SBC2-12-33-38	DX-SBC2-12-33/38-SS	DX-SBC2-12-33/38-B	3/4	33	38	
DX-SBC2-12-38-43	-	-	3/4	38	43	
DX-SBC4-08-23-26	-	-	1/2	23	26	4
DX-SBC4-16-35-40	-	-	1	35.5	40	
DX-SBC4-16-39-43	DX-SBC4-16-39/43-SS	DX-SBC4-16-39/43-B	1	39	43.5	
DX-SBC4-16-43-49	DX-SBC4-16-43/49-SS	DX-SBC4-16-43/49-B	1	43	49	
DX-SBC4-16-49-54	-	-	1	49	54	
DX-SBC4-20-38-45	-	-	1.1/4	38	45.5	
DX-SBC4-20-45-53	-	-	1.1/4	45.5	53	
DX-SBC4-20-54-60	DX-SBC4-20-54/60-SS	DX-SBC4-20-54/60-B	1.1/4	54	60	
DX-SBC4-24-46-51	-	-	1.1/2	46	51	
DX-SBC4-24-51-56	-	-	1.1/2	51	56	
DX-SBC4-24-55-60	DX-SBC4-24-55/60-SS	DX-SBC4-24-55/60-B	1.1/2	55.5	60	
DX-SBC4-24-60-65	DX-SBC4-24-60/65-SS	DX-SBC4-24-60/65-B	1.1/2	60	65	
DX-SBC4-24-65-70	-	-	1.1/2	65	70	
DX-SBC4-32-57-63	-	-	2	57	63.5	
DX-SBC4-32-59-64	-	-	2	59.5	64	
DX-SBC4-32-63-71	DX-SBC4-32-63/71-SS	DX-SBC4-32-63/71-B	2	63.5	71	
DX-SBC4-32-70-78	DX-SBC4-32-70/78-SS	DX-SBC4-32-70/78-B	2	70	78	
DX-SBC4-32-78-87	-	-	2	78.8	87.5	
DX-SBC4-40-78-87	-	-	2.1/2	78.5	87.5	
DX-SBC4-40-89-100	-	-	2.1/2	89	100	
DX-SBC4-48-89-100	-	-	3	89	100	
DX-SBC4-48-96-103	-	-	3	96.5	103	
DX-SBC4-48-103-113	-	-	3	103	113	
DX-SBC6-48-108-122	-	-	3	108	122	6
DX-SBC6-64-117-127	-	-	4	117.5	127	
DX-SBC6-64-123-133	-	-	4	123.5	133.5	
DX-SBC6-64-133-142	-	-	4	133.5	142	
DX-SBC6-64-140-151	-	-	4	140.5	151	
DX-SBC6-80-174-187	-	-	6	174.5	187	
DX-SBC6-80-190-203	-	-	6	190	203	

