

INDUSTRIAL HOSES - for automotive industry

Hoses



TUBANO

Material: Moulded EPDM rubber
Working temp: From -40°C up to +125°C

Hose used for cooling and heating installations, water, some acids and diluted alkalis. Resistant to high temperatures and ozone but with limited chemical resistance. Supplied in 1 m pieces to enable easy cutting and fitting into an installation.

code	I.D. [mm]	extensibility [mm]	working pressure [bar]	bending radius [mm]	standard length [m]
EC-102100	20	20 ÷ 25	1.5	70	1
EC-102101	25	25 ÷ 31	1.5	85	1
EC-102102	31.5	31.5 ÷ 36	1.5	105	1
EC-102103	33.5	33.5 ÷ 38	1.5	110	1
EC-102104	37	37 ÷ 44	1.5	115	1
EC-102105	44	44 ÷ 48	1.5	120	1
EC-102106	48	48 ÷ 55	1.5	125	1
EC-102107	55	55 ÷ 65	1.5	130	1
EC-102108	65	65 ÷ 75	1.5	140	1
EC-102109	80	80 ÷ 90	1.5	150	1



TUBANO OIL

Internal layer: Moulded EPDM rubber
External layer: Oil resistant synthetic rubber
Working temp.: From -40°C up to +125°C

Hose used for cooling and heating installations, water, some acids and diluted alkalis. Resistant to high temperatures and ozone but with limited chemical resistance. Supplied in 1 m pieces to enable easy cutting and fitting into an installation.

code	I.D. [mm]	extensibility [mm]	working pressure [bar]	bending radius [mm]	standard length [m]
EC-102111	20	20 ÷ 25	1.5	70	1
EC-102112	25	25 ÷ 31	1.5	85	1
EC-102113	31.5	31.5 ÷ 36	1.5	105	1
EC-102114	33.5	33.5 ÷ 38	1.5	110	1
EC-102115	37	37 ÷ 44	1.5	115	1
EC-102116	44	44 ÷ 48	1.5	120	1
EC-102117	48	48 ÷ 55	1.5	125	1
EC-102118	55	55 ÷ 65	1.5	130	1
EC-102119	65	65 ÷ 75	1.5	140	1