EC-type ends and connectors

KońbóEC cartridges are intendedą for crimping inężlow-pressureśpressure (with a maximum pressureśworking pressure of up to approx. 30 bar, depending ony hosenośof śdiameter), in particularólnośinężof rubber and plastic hoses, unreinforced and with textile reinforcement, with externalęsteel braid, etc. Crimped with sheet-metal ferrules usingą crimping machines for lineóin low-preśpressure (see sectionł „URZĄDEVICES AND ACCESSORIES").
In separatehosein relation to cońbóhydraulic actuators cońbóEC cartridges do not haveą lock łączącof the ferrulesę with cońbówką. Widely used in flexible lines for sanitary fittings, fuel and air installations, etc. EC ferrules caną być róexternallyy hose used for crimping fittingńbóshaft NiTO and cońbóquick coupling insertłąwhether.

Sheet-metal ferrule type H			
index (galv. steel)	diameter int. [mm]	hole diameter [mm]	length [mm]
EC-104040	9	5,7	17
EC-104050	10	6,7	17
EC-104051	11	6,7	17
EC-104060	11	7,7	17
EC-104062	12	7,7	20
EC-104064	12	10	20
EC-104082	12,5	9,6	15
EC-104063	13,5	7,7	20
EC-104080	13,5	10,2	20
EC-104084	14	10,2	20
EC-104065	15	7,6	20
EC-104106	15	11,5	16
EC-104085	15	10,2	20
EC-104105	15	11,8	20
EC-104100	16	11,9	20
EC-104107	17	11,9	21
EC-104118	18	13,9	21
EC-104112	19	14	26
EC-104120	20	14	26
EC-104121	20	13,5	20
EC-104158	22	15,4	20
EC-104122	22	15,7	32
EC-104123	23	17,2	32
EC-104124	24,5	17,2	33
EC-104126	26,5	19,7	32
EC-104128	28	20,7	34
EC-104130	30	24,2	32
EC-104132	32	23,7	34
EC-104133	33	24,2	34
EC-104136	34	25,9	34
EC-104138	36	27,5	35
EC-104140	38	28,3	35
EC-104142	40	30	40
EC-104145	45	35,1	37

Sheet-metal ferrule type H			
index (AISI 304)	diameter int. [mm]	hole diameter [mm]	length [mm]
EC-104260	11	7,5	17
EC-104262	12	7,5	20
EC-104278	12,5	10	20
EC-104280	13,5	10,1	20
EC-104284	14	9,7	20
EC-104305	15	11,7	20
EC-104300	16	11,7	20
EC-104307	17	12,2	21
EC-104318	18	13,8	21
EC-104312	19	13,8	26
EC-104319	22	15,6	26
EC-104323	23	18,7	28
EC-104327	29	20,8	30