








# HIGH PRESSURE - UHP equipment

## Connectors

Adapters intended to connect quick release couplings with UHP hoses and to connect to UHP porting blocks. Made of black zinc-plated steel.

picture	code	description	dimensions				press. [bar]		
			A	B	C	D			
	EU-RC15	dust plug	1/4" BSP 120°	-	28	22	2000		
	EU-RC34		3/4"-16 UNF 60°	-	32	22	3000		
	EU-RS15	straight connector with female thread	1/4" BSP 120°	1/4" BSP 120°	40	19	2000		
	EU-RS34		3/4"-16 UNF 60°	3/4"-16 UNF 60°	42	27	3000		
	EU-RN15	straight connector with male thread	1/4" BSP 120°	1/4" BSP 120°	46	22	2000		
	EU-RN29			1/4" NPT	43				
	EU-RN53			3/8" NPT	45				
	EU-RN17		1/4" BSP 60°	1/4" BSP 60°	34				
	EU-RN31			1/4" NPT	37				
	EU-RN55			3/8" NPT	39				
	EU-RN32		1/4" BSP 120°	1/4" BSP 60°	40	22	3000		
	EU-RN33		M16x1.5 60°		39				
	EU-RN28		3/4"-16 UNF 60°	1/2" BSP	44				
	EU-RN34			3/4"-16 UNF 60°	54				
	EU-RN34O			3/4"-16 UNF 60°	63				
	EU-RN49		3/4"-16 UNF 60°	1/4" BSP 120°	50				
	EU-RN51			1/4" BSP 60°	44				
	EU-RN50			M16x1.5 60°	50				
	EU-RR49	straight connector with male/female thread	3/4"-16 UNF 60°	1/4" BSP 120°	42			22	2000
	EU-RR51O		3/8" BSP 60°	1/2" BSP	53			27	3000
	EU-RE15	elbow connector	1/4" BSP 120°	12.5	35			35	2000
	EU-RE34		3/4"-16 UNF 60°	12.5	40			40	3000
	EU-RT15	tee connector	1/4" BSP 120°	12.5	40			40	2000
	EU-RT34		3/4"-16 UNF 60°	12.5	45			35	3000
	EU-RX15	cross connector	1/4" BSP 120°	-	45	45	2000		
	EU-RX34		3/4"-16 UNF 60°	-	55	55	3000		