








HIGH PRESSURE - UHP equipment

Connectors

Adapters intended to connect quick release couplings with UHP hoses and to connect to UHP porting blocks. Made of black zinc-plated steel.

Working pressure: 700 bar at safety factor 4:1, 1000 bar at safety factor 2.8:1.

picture	code	description	dimensions			
			A	B	C	D
	EU-RC14	dust plug	1/4" NPT	-	10.5	-
	EU-RC38		3/8" NPT	-		-
	EU-RS14	straight connector with female thread	1/4" NPT	1/4" NPT	32	19
	EU-RS38		3/8" NPT	3/8" NPT	34	24
	EU-RS52		1/4" NPT			
	EU-RN14	straight connector with male thread	1/4" NPT	1/4" NPT	39	17
	EU-RN38		3/8" NPT	3/8" NPT	41	
	EU-RN381				70	
	EU-RN382				120	
	EU-RN52		1/4" NPT	41		
	EU-RR23	straight connector with male/female thread	1/4" BSP 120°	3/8" NPT	41	24
	EU-RR24		1/4" NPT		40	
	EU-RR52		3/8" NPT	1/4" NPT	19	
	EU-RR02		1/2" BSP		22	
	EU-RR26		1/4" NPT		1/2" BSP	30
	EU-RR501		3/8" NPT			
			EU-RE14	elbow connector	1/4" NPT	15
EU-RE38		3/8" NPT	15		40	40
	EU-RT14	tee connector	1/4" NPT	12.5	40	35
	EU-RT38		3/8" NPT	15	45	40
	EU-RX14	cross connector	1/4" NPT	-	45	45
	EU-RX38		3/8" NPT	-		