



MACHINES AND ACCESSORIES - pneumatic accessories

Water and coolant guns for CNC machines


	code	connection	description
	EW-40404	13 mm hose tail	MULTICLEAN water gun with adjustable flow control and trigger lock. Solid brass construction. Particularly recommended for CNC machines, coolants and cleaning. Working press.: up to 40 bar. Working temp.: from +5°C up to +90°C. Weight: 1.05 kg.
	EW-40406	19 mm hose tail	
	EW-40430	1/2" female thread	
	EW-160K4	Ø 2 mm nozzle	Nozzle for MULTICLEAN gun. Ø 2 mm nozzle as a standard.
	EW-160K4A	Ø 4 mm nozzle	

	code	connection	description
	EW-41204	13 mm hose tail	PROFICLEAN water gun with adjustable flow control and trigger lock. Robust and lightweight aluminium construction. Particularly recommended for CNC machines, coolants and cleaning. Working press.: up to 25 bar. Working temp.: from +5°C up to +90°C. Weight: 0.75 kg.
	EW-41206	19 mm hose tail	
	EW-41230	1/2" female thread	
	EW-412K4	Ø 2 mm nozzle	Nozzle for PROFICLEAN gun. Ø 2 mm nozzle as a standard.
	EW-412K5	Ø 4 mm nozzle	

Pressure dependence of the flow rate, with a fully open valve

nozzle size	pressure [bar]					
	4	6	10	16	25	40
Ø 2 mm	4 l/min	5 l/min	6.3 l/min	8 l/min	10 l/min	13 l/min
Ø 4 mm	16 l/min	20 l/min	25 l/min	32 l/min	40 l/min	50 l/min

Gun for chassis cleaning

	code	connection	description
	EW-355511	quick release coupling plug	Water gun designed for chassis cleaning. Container: - EW-355511 - plastic 0.7 l. - EW-355521 - metal 0.7 l. - EW-355531 - none Max. pressure: 10 bar. Working pressure: 2+8 bar. Working temp.: +5°C up to +50°C.
	EW-355521	quick release coupling plug	
EW-355531	quick release coupling plug		