



EWO water and coolant guns for CNC machine tools

drawing	index	connection	description
	EW-40421	1/2" BSP female thread	Gun MULTICLEAN z flow control and trigger lever with protection. Robust, lightweight anodised aluminium construction colour black. Particularly suitable for CNC machine tools for coolant and for washing parts. Ø 2 mm nozzle in the gun. Operating pressure: up to 40 bar Operating temperature: +5°C to +90°C Weight: 1.02+ 1.2 kg (depending on version)
	EW-40422	EWO quick connector DN12 (EW-16020)	
	EW-40423	1/2" (13 mm) hose connector	
	EW-40424	3/4" (19 mm) hose connector	
	EW-160K4	nozzle Ø 2 mm (L=13 mm)	
	EW-160K4A	nozzle Ø 4 mm (L=13 mm)	Nozzle for MULTICLEAN gun. Nozzle Ø 2 mm as standard in the gun with O-ring. Material: brass Connection: GZ M21x1.5

drawing	index	connection	description
	EW-41621	1/2" BSP female thread	Gun PROFICLEAN z flow control and trigger lever with protection. Robust, lightweight aluminium construction. Especially recommended for CNC machine tools for coolants and for washing parts. Ø 2 mm nozzle in the gun. Operating pressure: 4 to 6 bar Maximum pressure: up to 25 bar Operating temperature: +5°C to +90°C Weight: 0.84 kg
	EW-41622	EWO quick connector DN12 (EW-16020)	
	EW-41623	1/2" (13 mm) hose connector	
	EW-41624	3/4" (19 mm) hose connector	
	EW-41699	nozzle Ø 2 mm (L=13 mm)	
	EW-41698	nozzle Ø 4 mm (L=13 mm)	Nozzle for gun PROFICLEAN. Nozzle Ø 2 mm as standard in the gun. Material: nickel-plated brass Connection: GZ M21x1.5 with O-ring.
	EW-41697	nozzle Ø 5.5 mm (L=13 mm)	
	EW-41696	nozzle Ø 4 mm (L=28 mm)	
	EW-41695	nozzle Ø 4 mm (L=58 mm)	

nozzle size	Flow rate of MULTICLEAN and PROFICLEAN guns as a function of pressure with fully open valve						
	pressure [bar]						
	4	6	10	16	20 (applies only to PROFICLEAN)	25 (applies only to MULTICLEAN)	40 (applies only to MULTICLEAN)
Ø 2 mm	4 l/min	5 l/min	6.3 l/min	8 l/min	10 l/min	10 l/min	13 l/min
Ø 4 mm	16 l/min	20 l/min	25 l/min	32 l/min	40 l/min	40 l/min	50 l/min

EWO water-air gun

drawing	index	Connection 1 (water)	Connection 2 (air)	description
	EW-165241	GZ 3/8" BSP	Quick connector DN7.2	POWERCLEAN water and air spray gun. Cleaning gun with adjustable nozzle. Air is used to increase the force of the jet. Powered by mains water or a container (e.g. bucket). Robust and lightweight aluminium construction. Nozzle Ø 6 mm as standard in the gun. Maximum pressure: up to 10 bar Operating temperature: +5°C to +50°C Flow rate (water, 4 bar): 36 l/min Flow rate (water, 10 bar): 56 l/min Weight: 0.77 kg
	EW-165441	plug garden	Quick connector DN7.2	

