

MACHINES AND ACCESSORIES - pneumatic accessories

EWO air blow guns



pic.	code	connection	description
1	EW-26941 ³⁾	DN 7.2 quick release coupling plug	General purpose blow gun designed for the removal of all kinds of dirt: fluid, chips, shavings, etc., from any surface. The flow is adjusted with a lever. The blow gun is equipped with STANDARD nozzle. Other nozzles can be also used - see „EWO blow gun accessories”. Material: anodised forged aluminium. Nozzle diameter: 1.5 mm. Nozzle connection: M12x1.25 male thread. Working press.: from 2 bar up to 8 bar. Max. working press.: 10 bar. Working temp.: from -10°C up to +50°C. 1) - cast aluminium. 2) - with a valve for maximum flow control. 3) - suitable for water.
2	EW-26941E ^{2), 3)}		
3	EW-26941L ¹⁾		
1	EW-26911 ³⁾	6 mm hose tail	
2	EW-26911E ^{2), 3)}		
3	EW-26911L ¹⁾		
1	EW-26917 ³⁾	10 mm hose tail	
2	EW-26917E ^{2), 3)}		
3	EW-26917L ¹⁾		
1	EW-26918 ³⁾	13 mm hose tail	
2	EW-26918E ^{2), 3)}		
3	EW-26918L ¹⁾		



pic.	code	connection	description
1	EW-269374	DN 7.2 quick release coupling plug	General purpose blow gun designed for the removal of all kinds of dirt: fluid, chips, shavings, etc., from any surface. The flow is adjusted with a lever. The blow gun is equipped with FULL-JET nozzle to provide the jet of air which is much wider in comparison to STANDARD nozzle. Other nozzles can be also used - see „EWO blow gun accessories”. Material: anodised forged aluminium. Nozzle diameter: 2.5 mm. Nozzle connection: M12x1.25 male thread. Working press.: from 2 bar up to 8 bar. Max. working press.: 10 bar. Working temp.: from -10°C up to +50°C. 1) - cast aluminium. 2) - with a valve for maximum flow control.
2	EW-269374E ²⁾		
3	EW-269374L ¹⁾		
1	EW-269324	6 mm hose tail	
2	EW-269324E ²⁾		
3	EW-269324L ¹⁾		
1	EW-269344	10 mm hose tail	
2	EW-269344E ²⁾		
3	EW-269344L ¹⁾		
1	EW-269354	13 mm hose tail	
2	EW-269354E ²⁾		
3	EW-269354L ¹⁾		