

INDUSTRIAL FITTINGS - quick release couplings


EWO couplings




EUROSTANDARD DN 7.2

- Standard:** Eurostandard DN 7.2 ÷ 7.8
- Application:** Pneumatics
(air, nitrogen, other nonflammable gases)
- Working press.:** 10 bar - max. 25 bar (safety factor 1.5)
- Flow rate:** 1000 l/min, Pe = 6 bar, Δp = 1 bar
- Working temp.:** From -20°C up to +80°C)
- Material:** Nickel-plated steel
- Advantages:** Swivel

Swivel plug with a design compliant with the popular EURO DN 7.2 standard. A full 360° rotation axis prevents twisting of a hose connected to the plug and enables unrestricted operation of pneumatic tools. In addition, the plug can be positioned (by 30° maximum) and thus easily fitted in tight and inaccessible spaces. Connected to the plug, the hose assembly will not kink. German quality added to a steel plug body plated with nickel provides significantly longer service life compared to standard brass plugs. The couplings are suitable for operation with percussive tools (pneumatic torque wrenches, nail guns, etc.). Interchangeable with all couplings according to Eurostandard DN 7.2 ÷ 7.8 of other producers.

	code	thread size [inch]	length [mm]	description
	EW-308-453	1/4	54.7	Plug with male thread
	EW-308-454	3/8	54.7	
	EW-308-457	1/2	56.7	

	code	thread size [inch]	length [mm]	description
	EW-308-455	1/4	54.7	Plug with female thread
	EW-308-456	3/8	54.7	
	EW-308-458	1/2	56.7	