

MACHINES AND ACCESSORIES - pneumatic accessories

EWO hand tyre inflators



PNEULIGHT

pic.	code	connector	description
1	EW-471221	lever	Hand-held tyre inflator designed for inflating tyres with air. It is equipped with 63 mm pressure gauge (accuracy class 1.6) in a rubber protection cover. This tyre inflator cannot be calibrated. A full range of accessories and spare parts is available (see: Hand tyre inflators - accessories). Material: blue polyamide (PA6 GK30). Connection: EUROSTANDARD 7.2 plug. Max. working press.: 10 bar. Working temp.: from -10°C up to +50°C.
2	EW-471223	clip	
3	EW-471222	double-sided push-on	
4	EW-471301	angle extension	



AIRMASTER STANDARD

pic.	code	connector	description
1	EW-356121	lever	Hand-held tyre inflator designed for inflating tyres with air and nitrogen. It is equipped with 63 mm pressure gauge (accuracy class 1.0) in a rubber protection cover with double scale (bar, psi). This tyre inflator cannot be calibrated. A full range of accessories and spare parts is available (see: Hand tyre inflators - accessories). Material: aluminium. Connection: EUROSTANDARD 7.2 plug (* - DN 6 hose tail). Working press.: up to 10 bar. Max. working press.: 12 bar. Working temp.: from -10°C up to +60°C.
2	EW-356123	clip	
3	EW-356122	double-sided push-on	
1	EW-356111*	lever	
2	EW-356113*	clip	
3	EW-356112*	double-sided push-on	