EWO water and coolant guns for CNC machine tools

drawing	index	connection	description
	EW-40421	female thread 1/2" BSP	**MULTICLEAN gun** with flow adjustment and safety trigger lever. Sturdy, lightweight construction of black-anodised aluminium. Particularly recommended for CNC machine tools for coolant and for washing parts. The gun has a Ø 2 mm nozzle. Working pressure: up to 40 bar Working temp.: from +5ºC to +90ºC Weight: 1.02 ÷ 1.2 kg (depending on version)
	EW-40422	EWO DN12 quick coupling plug	
	EW-40423	hose end for 1/2" hose (13 mm)	
	EW-40424	hose end for 3/4" hose (19 mm)	
	EW-160K4	nozzle Ø 2 mm (L=13 mm)	**Nozzle for MULTICLEAN gun.** Standard gun nozzle Ø 2 mm with O-ring. Material: brass Connection: male thread M21x1.5
	EW-160K4A	nozzle Ø 4 mm (L=13 mm)	

drawing	index	connection	description
	EW-41621	female thread 1/2" BSP	**PROFICLEAN gun** with flow adjustment and safety trigger lever. Sturdy, lightweight aluminium construction. Particularly recommended for CNC machine tools for coolant and for washing parts. The gun has a Ø 2 mm nozzle. Operating pressure: from 4 to 6 bar Maximum pressure: up to 25 bar Working temp.: from +5ºC to +90ºC Weight: 0.84 kg
	EW-41622	EWO DN12 quick coupling plug	
	EW-41623	hose end for 1/2" hose (13 mm)	
	EW-41624	hose end for 3/4" hose (19 mm)	
	EW-41699	nozzle Ø 2 mm (L=13 mm)	**Nozzle for PROFICLEAN gun**. Standard gun nozzle Ø 2 mm. Material: nickel-plated brass Connection: male thread M21x1.5 with O-ring.
	EW-41698	nozzle Ø 4 mm (L=13 mm)	
	EW-41697	nozzle Ø 5.5 mm (L=13 mm)	
	EW-41696	nozzle Ø 4 mm (L=28 mm)	
	EW-41695	nozzle Ø 4 mm (L=58 mm)	

size nozzle	Flow rate for MULTICLEAN and PROFICLEAN guns depending on pressure with valve fully open						
	pressure [bar]						
	4	6	10	16	20 (re. PROFICLEAN)	25 (re. MULTICLEAN)	40 (re. MULTICLEAN)
Ø 2 mm	4 l/min	5 l/min	6.3 l/min	8 l/min	10 l/min	10 l/min	13 l/min
Ø 4 mm	16 l/min	20 l/min	25 l/min	32 l/min	40 l/min	40 l/min	50 l/min

EWO water-air gun

drawing	index	connection 1 (water)	connection 2 (air)	description
	EW-165241	GZ 3/8" BSP	plug quick couplings DN7,2	**POWERCLEAN water-air gun.** Cleaning gun with adjustable nozzle. Air is used to increase jet force. Supplied with mains water or from a container (e.g. a bucket). Sturdy and lightweight aluminium construction. The gun comes standard with a Ø 6 mm nozzle. Maximum pressure: up to 10 bar Working temp.: from +5ºC to +50ºC Flow (water, 4 bar): 36 l/min Flow (water, 10 bar): 56 l/min Weight: 0.77 kg
	EW-165441	garden plug	plug quick couplings DN7,2	