

# MACHINES AND ACCESSORIES - pneumatic accessories

## EWO air blow guns - accessories

The accessories below are intended for the following blow guns :  
STANDARD, FULL-JET, BLOWSTAR, SAFETYSTAR, EWO 470.



pic.	code	description
1	EW-470K61	6 hole, flat nozzle with M12x1.25 male thread, material: blue polyamide; max. press.: 6 bar; work. temp.: -10°C to +50°C.
2	EW-470K60	16 hole, flat nozzle with M12x1.25 male thread, material: blue polyamide; max. press.: 6 bar; work. temp.: -10°C to +50°C.
3	EW-105K6	Standard nozzle, 1.5 mm diameter, with centered hole and high blowing power; noise level 85 dB at pressure above 4 bar.
	EW-105K7	Standard nozzle, 2 mm diameter, with centered hole and high blowing power; noise level 90 dB at pressure above 4 bar.
4	EW-269K33	Nozzle with built-in silencer, with wide air jet and low noise level - below 70 dB.
5	EW-269K45	FULL-JET injector nozzle, 2 mm diameter, made of polyamide, with wide air jet and low noise level - below 90 dB.
6	EW-269K59	FULL-JET injector nozzle, 2.5 mm diameter, made of aluminium, with wide air jet and low noise level - below 90 dB.
7	EW-105K45	Bicycle nozzle.
8	EW-269K27	Nozzle with air shield protects operator against small particles of dirt during cleaning operations and dampens noise.
9	EW-470K37	BLOWSTAR nozzle (without double nipple) features very low noise level, down to hardly 74 dB at 6 bar pressure, with no impact on blowing power.
-	EW-470K38	Double nipple (1/4" x M12x1.25 male thread).
9	EW-470K39	BLOWSTAR nozzle (with double nipple) features very low noise level, down to hardly 74 dB at 6 bar pressure, with no impact on blowing power.
10	EW-470K12	110 mm bent extension nozzle, 2.3 mm diameter, nickel-plated steel.
11	EW-470K43	SAFETYSTAR 120 mm bent extension nozzle, nickel-plated steel, noise reduction down to 80 dB.
12	EW-105K16A	110 mm bent extension nozzle, nickel-plated brass.
	EW-105K14A	160 mm bent extension nozzle, nickel-plated brass.
	EW-105K15A	260 mm bent extension nozzle, nickel-plated brass.
13	EW-105K103	115 mm straight extension nozzle, nickel-plated brass.
	EW-105K104	165 mm straight extension nozzle, nickel-plated brass.
	EW-105K105	265 mm straight extension nozzle, nickel-plated brass.
	EW-105K107	415 mm straight extension nozzle, nickel-plated brass.
14	EW-26915	Safety shield, 70 mm diameter (to be mounted between nozzle and gun).