

MACHINES AND ACCESSORIES - pneumatic accessories

EWO impact wrench



741 Series

Top quality impact wrench designed for mounting and dismounting wheels - for service stations, car workshops, tyre fitting, repair and replacement services. As an assembly tool, it is commonly used when handling steel constructions, machines, etc.

Basic features:

- TWIN HAMMER - twin impact mechanism,
- housing made of durable composite materials,
- handle covered with anti vibration material,
- low noise level - 83dB(A),
- 3-stage power settings for different torque.

parameters	code		
	EW-741130	EW-741160	EW-741180
Square drive	3/8" (10 mm)	1/2" (13 mm)	1/2" (13 mm)
Maximum free speed [rev./min]	11000	11000	7000
Working torque [Nm]	583	624	1112
Maximum free torque [Nm]	678	678	1756
Working torque range [Nm]	34 ÷ 338	34 ÷ 338	68 ÷ 746
Average air consumption [l/min]	113	113	113
Recommended working pressure [bar]	6.2	6.2	6.3
Connection [inch]	1/4 BSP female	1/4 BSP female	1/4 BSP female
Weight [kg]	1.2	1.2	1.9

Accessories

picture	code	description
	EW-741100	Set of 1/2" sockets: 17, 19 and 21 mm in a box. Compatible with EW-741160 and EW-741180 impact wrench.
	EW-31710	Small lubricator intended to lubricate pneumatic tools with oil mist in order to protect it against corrosion, reduce friction and prevent premature wearing of parts. Oil (code: EW-583) must be ordered separately Working press.: 0.5 ÷ 10 bar, Tank volume: 5.5 cm ³ , Dimensions: 35 x 60 mm.
	EW-E40702	Flexible hose assembly comprised of SOFTPLUS hose, with 1/4" BSP female thread fitting and EUROSTANDARD 7.2 plug. Intended to connect pneumatic tools. Dampens vibration. Diameter: 9 mm, Length: 200 mm, Working press.: up to 15 bar.