


# INDUSTRIAL FITTINGS - quick release couplings

## EWO couplings



### MIKRO DN 2.7

**Standard:** GLOBAL DN 2.7  
**Application:** Pneumatics  
 (air, nitrogen, other nonflammable gases)  
**Working press.:** 16 bar (safety factor 1.5)  
**Flow rate:** 210 l/min, Pe = 6 bar, Δp = 1bar  
**Working temp.:** From -20°C up to +100°C)  
**Material:** Nickel-plated brass, pins and spring of SS  
**Seal:** NBR  
**Advantages:** Small size

Single shut-off MICRO quick release coupling is widely used for applications demanding small dimensions e.g. in medical, laboratory or measuring technology. Designed for one hand operation. Interchangeable with RECTUS 20 and all DN 2.7 quick release couplings of other producers with the same plug design.

	code	hose I.D. [mm]	length [mm]	spanner size [mm]	description
	EW-MIKRO-GK-03	3	35	-	Socket with hose tail.
	EW-MIKRO-GK-04	4	35	-	
	code	hose O.D. x I.D. [mm]	length [mm]	spanner size [mm]	description
	EW-MIKRO-GK-4x3	4x3	34	9	Socket with plastic hose tail.
	EW-MIKRO-GK-5x3	5x3	34	9	
	EW-MIKRO-GK-6x4	6x4	34	9	
	code	thread size	length [mm]	spanner size [mm]	description
	EW-MIKRO-GZ-M5	M5	26	9	Socket with male thread.
	EW-MIKRO-GZ-02	1/8"	28	11	
	code	thread size	length [mm]	spanner size [mm]	description
	EW-MIKRO-GW-M5	M5	25	9	Socket with female thread.
	EW-MIKRO-GW-02	1/8"	28	12	
	code	hose I.D. [mm]	length [mm]	spanner size [mm]	description
	EW-MIKRO-WK-03	3	25	-	Plug with hose tail.
	EW-MIKRO-WK-04	4	25	-	
	code	hose O.D. x I.D. [mm]	length [mm]	spanner size [mm]	description
	EW-MIKRO-WK-4x3	4x3	25	7	Plug with plastic hose tail.
	EW-MIKRO-WK-5x3	5x3	25	7	
	EW-MIKRO-WK-6x4	6x4	24	-	
	code	thread size	length [mm]	spanner size [mm]	description
	EW-MIKRO-WZ-M5	M5	18	7	Plug with male thread.
	EW-MIKRO-WZ-02	1/8"	20	11	
	code	thread size	length [mm]	spanner size [mm]	description
	EW-MIKRO-WW-M5	M5	17	7	Plug with female thread.
	EW-MIKRO-WW-02	1/8"	18	12	