

INDUSTRIAL FITTINGS - fittings, connectors

Brass connectors - EW type

Working press.: Up to 63 bar

Working temp.: From -10°C up to +90°C

90°elbow, BSP male



code	size	thread size [inch]	spanner size [mm]
EW-MS-18582	5	1/8	10
EW-MS-18583	7	1/4	13
EW-MS-18585	8	3/8	17
EW-MS-18587	12	1/2	21
EW-MS-18588*	19	3/4	25
EW-MS-18589*	25	1	30

90°elbow, BSP female / male



code	size	thread size [inch]	spanner size [mm]
EW-MS-18542	6	1/8	10
EW-MS-18543	8	1/4	13
EW-MS-18545	11	3/8	17
EW-MS-18547	15	1/2	21
EW-MS-18548	19	3/4	25
EW-MS-18549	25	1	30

Tee, BSP male



code	size	thread size [inch]	spanner size [mm]
EW-MS-18597	5	1/8	10
EW-MS-18596	8	1/4	13
EW-MS-18595	9	3/8	17
EW-MS-18594	12	1/2	21
EW-MS-18593*	19	3/4	25
EW-MS-18592*	25	1	30

Tee, BSP female / male / female



code	size	thread size [inch]	spanner size [mm]
EW-MS-18562	6	1/8	10
EW-MS-18563	8	1/4	13
EW-MS-18565	11	3/8	17
EW-MS-18567	15	1/2	21
EW-MS-18568	19	3/4	25
EW-MS-18569	25	1	30

Tee, BSP female / female / male



code	size	thread size [inch]	spanner size [mm]
EW-MS-18512	6	1/8	10
EW-MS-18513	8	1/4	13
EW-MS-18515	15	3/8	17
EW-MS-18517	19	1/2	21
EW-MS-18518*	25	3/4	25
EW-MS-18519*	30	1	33

Tee, BSP female



code	size	thread size [inch]
EW-MS-185197	8	1/8
EW-MS-185196	11	1/4
EW-MS-185195	15	3/8
EW-MS-185194	19	1/2
EW-MS-185193	25	3/4
EW-MS-185192	30	1

* - without internal cone