



FINN-POWER hydraulic presses - service (P16)

TUBES INTERNATIONAL[®] is the only authorised distributor of FINN-POWER hydraulic presses in Poland. It provides technical consultancy, sales, training, warranty and post-warranty service.

FINN-POWER
Crimping since 1973

Portable FINN-POWER presses, are designed to perform repairs in the field, at the place of failure. FINN-POWER service presses are simple in design, easy to operate and are reliable. The low weight allows easy transport to any location. They are designed for repair workshops, technical trucks, service points. In the P16 presses made in the "Z" version, the drive unit is connected to the press head by a flexible 3 m cable.



FP-P16HP

Type	P16HP	P16AP	P16HPZ	P16APZ
clamp diameter range ¹⁾	up to 45 mm			
maximum clamping force	95 T			
max. internal diameter of hose clamps	1" (25 mm)			
jaws	type 16			
max. jaw opening ²⁾	+ 20 mm			
Main jaws D/L	39 / 64 mm			
control ³⁾	manual			
motor / drive ⁴⁾	manual	pneumatic	manual	pneumatic
dimensions (L x W x H) mm	331x401x271	331x346x271	-	-
weight (with oil)	26 kg	28 kg	28 kg	28 kg



FP-P16AP

- ¹⁾With standard jaws. The clamping range can be extended by using special jaws.
²⁾This is the total stroke of the jaws. The minimum clamping diameter of the jaws used must be added to this value.
³⁾Knob for setting the clamp diameter, together with an electrical indicator that it has been reached.
⁴⁾Determines how the hydraulic pump is driven.



FP-P16HPZ

STANDARD JAW TYPE 16				
index	clamping diameter range [mm]	drawing	D [mm]	L [mm]
FP-16-10	10,0 - 12,0		10	55
FP-16-12	12,0 - 14,0		12	55
FP-16-14	14,0 - 16,0		14	55
FP-16-16	16,0 - 19,0		16	55
FP-16-19	19,0 - 23,0		19	55
FP-16-23	23,0 - 27,0		23	55
FP-16-27	27,0 - 31,0		27	55
FP-16-31	31,0 - 38,0		31	65
Main jaws	38,0 - 45,0		39	64



FP-P16APZ

AIR CONDITIONING JAWS TYPE 16 ACFP			
index	drawing	D min [mm]	L [mm]
FP-16ACFP-04F		13,5	46,5
FP-16ACFP-06F		15,5	46,5
FP-16ACFP-08F		18,5	46,5
FP-16ACFP-10F		20,5	46,5

