



Threaded couplings under shell bracket EN 14420-3 / DIN 2817

VSLR coupling with BSP male thread for corrugated tail shell bracket

Seal: flat (butt joint)

Hose inside diameter		thread size [inch]	material	index	weight [kg]	drawing	
[inch].	[mm].						
1"	25	1" BSP	AISI 316 steel	GD-VSLRB-025-025-SS	0,198	 stainless steel AISI 316 (GD-VSLRB-050-050-SS)	
			brass	GD-VSLRB-025-025-MS	0,119		
1.1/4"	32	1.1/4" BSP	AISI 316 steel	GD-VSLRB-032-032-SS	0,265		
			brass	GD-VSLRB-032-032-MS	0,178		
1.1/2"	38	1.1/2" BSP	AISI 316 steel	GD-VSLRB-038-038-SS	0,358		
			brass	GD-VSLRB-038-038-MS	0,231		
2"	50	2" BSP	AISI 316 steel	GD-VSLRB-050-050-SS	0,5		
			brass	GD-VSLRB-050-050-MS	0,349		
2.1/2"	63 ÷ 65	2.1/2" BSP	AISI 316 steel	GD-VSLRB-063-063-SS	0,858		 brass (GD-VSLRB-050-050-MS)
			brass	GD-VSLRB-063-063-MS	0,599		
3"	75	3" BSP	AISI 316 steel	GD-VSLRB-080-075-SS	1,251		
			brass	GD-VSLRB-080-075-MS	0,888		
4"	100	4" BSP	AISI 316 steel	GD-VSLRB-100-100-SS	~		
			brass	GD-VSLRB-100-100-MS	1,892		

MSLR coupling with BSP female thread under corrugated tail shell clamp

Sealing: flat gasket (included, standard polyurethane, for stainless steel PTFE)

Hose inside diameter		thread size [inch]	material	index	weight [kg]	drawing	
[inch].	[mm].						
1"	25	1" BSP	AISI 316 steel	GD-MSLRB-025-025-SS	0,095	 stainless steel AISI 316 (GD-MSLRB-050-050-SS)	
			brass	GD-MSLRB-025-025-MS	0,106		
1.1/4"	32	1.1/4" BSP	AISI 316 steel	GD-MSLRB-032-032-SS	0,157		
			brass	GD-MSLRB-032-032-MS	0,174		
1.1/2"	38	1.1/2" BSP	AISI 316 steel	GD-MSLRB-038-038-SS	0,235		
			brass	GD-MSLRB-038-038-MS	0,261		
2"	50	2" BSP	AISI 316 steel	GD-MSLRB-050-050-SS	0,448		
			brass	GD-MSLRB-050-050-MS	0,498		
2.1/2"	63 ÷ 65	2.1/2" BSP	AISI 316 steel	GD-MSLRB-063-063-SS	0,558		 brass (GD-MSLRB-050-050-MS)
			brass	GD-MSLRB-063-063-MS	0,620		
3"	75	3" BSP	AISI 316 steel	GD-MSLRB-080-075-SS	0,912		
			brass	GD-MSLRB-080-075-MS	1,013		
4"	100	4" BSP	AISI 316 steel	GD-MSLRB-100-100-SS	1,310		
			brass	GD-MSLRB-100-100-MS	1,456		

