







Symmetrical connectors NOR standard (Norway)

	index	DN of coupling [mm]	spacing [mm]	tip diameter [mm]	description
	GP-NOR1040038-B	40	50	38	Coupling with hose end. Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-NOR1050038-B	50	66	38	
	GP-NOR1050052-B	50	66	52	
	GP-NOR1065038-B	65	83	38	
	GP-NOR1065052-B	65	83	52	
	GP-NOR1065064-B	65	83	64	

	index	DN of coupling [mm]	spacing [mm]	thread diameter [inch]	description
	GP-NOR2040025-B	40	50	1	Adapter with BSP female thread.
	GP-NOR2040050-B	40	50	2	
	GP-NOR2050038-B	50	66	1.1/2	Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-NOR2050050-B	50	66	2	
	GP-NOR2065038-B	65	83	1.1/2	
	GP-NOR2065050-B	65	83	2	
GP-NOR2065065-B	65	83	2.1/2		

	index	DN of coupling [mm]	spacing [mm]	thread diameter [inch]	description
	GP-NOR3040032-B	40	50	1.1/4	Adaptor with BSP male thread.
	GP-NOR3050038-B	50	66	1.1/2	
	GP-NOR3050050-B	50	66	2	Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-NOR3065038-B	65	83	1.1/2	
	GP-NOR3065050-B	65	83	2	
	GP-NOR3065065-B	65	83	2.1/2	

	index	DN of coupling [mm]	spacing [mm]	description
	GP-NOR4040050-B	40	50	Cap with chain. Material: bronze. Operating pressure: 10 bar.
	GP-NOR4050066-B	50	66	
	GP-NOR4065083-B	65	83	

	index	DN of coupling [mm]	description
	GP-NOR5040	40	Gasket. Material: NBR rubber.
	GP-NOR5050	50	
	GP-NOR5065	65	

