







Symmetrical connectors standard ROTTA ROTH (Russia)

	index	DN of coupling [mm]	spacing [mm]	tip diameter [mm]	description
	GP-ROTH1050038-B	50	68	38	Coupling with hose end. Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-ROTH1050052-B	50	68	52	
	GP-ROTH1070052-B	70	85	52	
GP-ROTH1070064-B	70	85	64		

	index	DN of coupling [mm]	spacing [mm]	thread size [inch]	description
	GP-ROTH2050038-B	50	68	1.1/2	Adapter with BSP female thread. Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-ROTH2050050-B	50	68	2	
	GP-ROTH2070050-B	70	85	2	
GP-ROTH2070065-B	70	85	2.1/2		

	index	DN of coupling [mm]	spacing [mm]	thread size [inch]	description
	GP-ROTH3050038-B	50	68	1.1/2	Adaptor with BSP male thread. Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
GP-ROTH3050050-B	50	68	2		

	index	DN of coupling [mm]	spacing [mm]	description
	GP-ROTH4050068-B	50	68	Cap with chain. Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
GP-ROTH4070085-B	70	85		

	index	DN of coupling [mm]	description
	GP-ROTH5050	50	Gasket. Material: NBR rubber.
GP-ROTH5070	70		

