







**Symmetric connectors SMS standard (Sweden)**

	index	DN of coupling [mm]	spacing [mm]	tip diameter [mm]	description
	GP-SMS1032038-B	32	41	38	Coupling with hose end. Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-SMS1063038-B	63	76	38	
	GP-SMS1063052-B	63	76	52	
	GP-SMS1063064-B	63	76	64	

	index	DN of coupling [mm]	spacing [mm]	thread size [inch]	description
	GP-SMS2032025-B	32	41	1	Adapter with BSP female thread.  Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-SMS2032050-B	32	41	2	
	GP-SMS2063025-B	63	76	1	
	GP-SMS2063038-B	63	76	1.1/2	
	GP-SMS2063050-B	63	76	2	
GP-SMS2063065-B	63	76	2.1/2		

	index	DN of coupling [mm]	spacing [mm]	thread size [inch]	description
	GP-SMS3032050-B	32	41	2	Adaptor with BSP male thread.  Material: bronze. Operating pressure: 10 bar. Gasket: NBR rubber.
	GP-SMS3063050-B	32	76	2	

	index	DN of coupling [mm]	spacing [mm]	description
	GP-SMS4032041-B	32	41	Cap with chain. Material: bronze. Operating pressure: 10 bar.
GP-SMS4063076-B	63	76		

	index	DN of coupling [mm]	description
	GP-SMS5032	32	Gasket.  Material: NBR rubber.
GP-SMS5063	63		

