

CLEANING AND WASHING - high pressure

Hoses for high pressure cleaning equipment



FORTRESS 1000®

Internal layer: Black NBR rubber compound
Reinforcement: Synthetic cord
External layer: Blue Carbryn® rubber protected by Microban® cover
Working temp.: From -30°C up to +93°C

High-quality, flexible, non-staining, kink and torsion resistant hose. Widely used for washdown applications in food, pharmaceutical and cosmetic industry due to Microban® antimicrobial external protection layer that inhibits the growth of bacteria, mold, and fungi. In compliance with ISO 1307. Use with hydraulic fittings (TI-Z...) crimped with appropriate ferrules.

code	I.D. [mm]	O.D. [mm]	working pressure [bar]	bursting pressure [bar]	weight [kg/m]	standard length [m]
GY-FORT1000-10	9.5	19.1	69	276	0.27	152.5
GY-FORT1000-13	12.7	21.8	69	276	0.30	152.5
GY-FORT1000-19	19.1	30.5	69	276	0.63	152.5



FORTRESS 3000®

Internal layer: Black NBR rubber compound
Reinforcement: Synthetic cord
External layer: Blue Carbryn® rubber protected by Microban® cover
Working temp.: From -30°C up to +93°C

High-quality, flexible, non-staining, kink and torsion resistant hose. Widely used for washdown applications in food, pharmaceutical and cosmetic industry due to Microban® antimicrobial external protection layer that inhibits the growth of bacteria, mold, and fungi. In compliance with ISO 1307. Use with hydraulic fittings (TI-Z...) crimped with appropriate ferrules.

code	I.D. [mm]	O.D. [mm]	working pressure [bar]	bursting pressure [bar]	weight [kg/m]	standard length [m]
GY-FORT3000-06	6.4	13.5	207	828	0.22	152.5
GY-FORT3000-10	9.5	17.5	207	828	0.36	152.5
GY-FORT3000-13	12.7	20.8	207	828	0.48	152.5