

UHP ready hoses: SPIR STAR[®] and WATERBLAST rubber in 24 hours

Ready-to-use, complete, tested UHP (ULTRA HIGH PRESSURE) hoses from selected SPIR STAR[®] and WATERBLAST hoses, with selected, most popular ends and in the most popular lengths (Lc). Full information on the parameters of the hoses used can be found on the preceding pages of the catalogue (WATERBLAST rubber hose data in the "WATERBLAST hoses" section). Hoses are available within 24 hours, subject to the following rules:

- confirmation of stock availability of cable;
- order at a Tubes International branch and agree the technical and commercial side by 12.00 on the day before the completed cable is available for collection or dispatch;
- reconciliation completed with an order confirmation received by the customer.



drawing	cable index	Hose type	inside diameter [mm]	working pressure [bar]	total length [m]	tips				
						left	fig.	rights	fig.	
hydraulics 700 bar										
	HASS-06-001-L1M	SS-HL-VIPER-06	6,1	700	1	GZ 3/8" NPT	1	GZ 3/8" NPT	1	
	HASS-06-001-L2M	SS-HL-VIPER-06			2					
	HASS-06-001-L3M	SS-HL-VIPER-06			3					
	HASS-06-001-L5M	SS-HL-VIPER-06			5					
	HASS-06-001-L10M	SS-HL-VIPER-06			10					
hydraulics 1800 bar										
	HASS-05-002-L2M	SS-NW-05-4	5	1800	2	GW 1/4" BSP	2	GW 1/4" BSP	2	
	HASS-05-002-L3M	SS-NW-05-4	5	1800	3	GW 1/4" BSP	2	GW 1/4" BSP	2	
	HASS-05-002-L5M	SS-NW-05-4	5	1800	5	GW 1/4" BSP	2	GW 1/4" BSP	2	
cleaning 1000 bar										
	HAWB-13-001-L20M	SL-WBL1100-13	12,7	1100	20	GW M24x1.5	4	GW M24x1.5	4	
	HAWB-19-002-L20M	SL-WBL1100-19	19	1100	20	GW M36x2	4	GW M36x2	4	
	HASS-08-003-L20M	SS-NW-08-2W	8	1040	20	GW M24x1.5	4	GW M24x1.5	4	
	HASS-03-004-L12M	SS-NW-03-2	3,4	1000	12	GW 1/4" BSP	2	GZ M7x1 flat	5	
	HASS-04-005-L12M	SS-NW-04-2	4	1200	12	GW M24x1.5	4	PG 1/8" BSP flat	6	
	HASS-05-006-L12M	SS-NW-05-2	5	1040	12	GW M24x1.5	4	PG 1/8" BSP flat	6	
	HASS-06-007-L12M	SS-NW-06-2	6,3	1000	12	GW M24x1.5	4	Socket 1/4" BSP flat	6	
cleaning 2500 bar										
	HASS-08-008-L20M	SS-NW-08-6H	7,7	2500	20	9/16"-18 UNF LH	3	9/16"-18 UNF LH	3	
	HASS-08-009-L20M	SS-NW-08-6H	7,7	2500	20	GZ HPM14x1.5LH	3	GZ HPM14x1.5LH	3	
	HASS-05-010-L5M	SS-NW-05-6	4,8	2500	5	9/16"-18 UNF LH	3	9/16"-18 UNF LH	3	
	HASS-05-011-L5M	SS-NW-05-6	4,8	2500	5	GZ HP M14x1.5LH	3	GZ HP M14x1.5LH	3	
cleaning 2800 bar										
	HASS-08-012-L20M	SS-NW-08-6UHP	7,6	2800	20	9/16"-18 UNF LH	3	9/16"-18 UNF LH	3	
	HASS-08-013-L20M	SS-NW-08-6UHP	7,6	2800	20	GZ HP M14x1.5LH	3	GZ HP M14x1.5LH	3	
	HASS-05-014-L5M	SS-NW-05-6H	4,8	2800	5	9/16"-18 UNF LH	3	9/16"-18 UNF LH	3	
	HASS-05-015-L5M	SS-NW-05-6H	4,8	2800	5	GZ HPM14x1.5LH	3	GZ HP M14x1.5LH	3	
cleaning 3000 bar										
	HASS-08-016-L20M	SS-NW-08-6UHP-X	7,6	3035	20	9/16"-18 UNF LH	3	9/16"-18 UNF LH	3	
	HASS-08-017-L20M	SS-NW-08-6UHP-X	7,6	3035	20	GZ HP M14x1.5LH	3	GZ HP M14x1.5LH	3	
	HASS-05-018-L5M	SS-NW-05-8UHP	4,5	3200	5	9/16"-18 UNF LH	3	9/16"-18 UNF LH	3	
	HASS-05-019-L5M	SS-NW-05-8UHP	4,5	3200	5	GZ HP M14x1.5 LH	3	GZ HP M14x1.5 LH	3	

