
DIN2353 fittings

GE – MB – S





Male thread type **G:**

METRIC

Straight fitting


Sealing method: sealing lip (metal - metal) DIN 3852-**B**

Safety factor: **2,5:1**

series	D [mm]	M [mm]	G	galvanised steel		Zn-Ni zinc-plated steel		galvanised steel Guardian Seal®		AISI 316 stainless steel	
				index	P [bar]	index	P [bar]	index	P [bar]	index	P [bar]
S	6	14x1,5	12x1,5	HD-GE-06S-MB-12	630	HD-GE-06S-MB-12-CN	630	HD-GE-06S-MB-12-W	630	HD-GE-06S-MB-12-SS	630
	6	14x1,5	14x1,5	-	-	-	-	-	-	HD-GE-06S-MB-14-SS	630
	8	16x1,5	12x1,5	-	-	HD-GE-08S-MB-12-CN	630	-	-	-	-
	8	16x1,5	14x1,5	HD-GE-08S-MB-14	630	HD-GE-08S-MB-14-CN	630	HD-GE-08S-MB-14-W	630	HD-GE-08S-MB-14-SS	630
	10	18x1,5	14x1,5	-	-	HD-GE-10S-MB-14-CN	630	-	-	-	-
	10	18x1,5	16x1,5	HD-GE-10S-MB-16	630	HD-GE-10S-MB-16-CN	630	HD-GE-10S-MB-16-W	630	HD-GE-10S-MB-16-SS	630
	10	18x1,5	18x1,5	-	-	HD-GE-10S-MB-18-CN	630	-	-	HD-GE-10S-MB-18-SS	630
	12	20x1,5	12x1,5	-	-	-	-	-	-	HD-GE-12S-MB-12-SS	630
	12	20x1,5	14x1,5	-	-	-	-	-	-	HD-GE-12S-MB-14-SS	630
	12	20x1,5	16x1,5	-	-	HD-GE-12S-MB-16-CN	630	-	-	HD-GE-12S-MB-16-SS	630
	12	20x1,5	18x1,5	HD-GE-12S-MB-18	630	HD-GE-12S-MB-18-CN	630	HD-GE-12S-MB-18-W	630	HD-GE-12S-MB-18-SS	630
	12	20x1,5	22x1,5	-	-	HD-GE-12S-MB-22-CN	630	-	-	HD-GE-12S-MB-22-SS	400
	12	20x1,5	27x2	-	-	HD-GE-12S-MB-27-CN	630	-	-	-	-
	14	22x1,5	18x1,5	-	-	HD-GE-14S-MB-18-CN	630	-	-	-	-
	14	22x1,5	20x1,5	HD-GE-14S-MB-20	630	HD-GE-14S-MB-20-CN	630	-	-	HD-GE-14S-MB-20-SS	630
	16	24x1,5	18x1,5	HD-GE-16S-MB-18	630	HD-GE-16S-MB-18-CN	630	-	-	HD-GE-16S-MB-18-SS	400
	16	24x1,5	22x1,5	HD-GE-16S-MB-22	630	HD-GE-16S-MB-22-CN	630	HD-GE-16S-MB-22-W	630	HD-GE-16S-MB-22-SS	400
	16	24x1,5	27x2	-	-	HD-GE-16S-MB-27-CN	400	-	-	-	-
	20	30x2	18x1,5	-	-	HD-GE-20S-MB-18-CN	400	-	-	-	-
	20	30x2	22x1,5	HD-GE-20S-MB-22	400	HD-GE-20S-MB-22-CN	400	-	-	-	-
	20	30x2	27x2	HD-GE-20S-MB-27	400	HD-GE-20S-MB-27-CN	400	HD-GE-20S-MB-27-W	400	HD-GE-20S-MB-27-SS	400
	20	30x2	33x2	-	-	HD-GE-20S-MB-33-CN	400	-	-	-	-
	25	36x2	27x2	HD-GE-25S-MB-27	400	HD-GE-25S-MB-27-CN	400	-	-	-	-
	25	36x2	33x2	HD-GE-25S-MB-33	400	HD-GE-25S-MB-33-CN	400	HD-GE-25S-MB-33-W	400	HD-GE-25S-MB-33-SS	400
	30	42x2	33x2	HD-GE-30S-MB-33	200	HD-GE-30S-MB-33-CN	200	-	-	-	-
	30	42x2	42x2	HD-GE-30S-MB-42	200	HD-GE-30S-MB-42-CN	200	HD-GE-30S-MB-42-W	200	HD-GE-30S-MB-42-SS	250
	38	52x2	48x2	HD-GE-38S-MB-48	200	HD-GE-38S-MB-48-CN	200	HD-GE-38S-MB-48-W	200	HD-GE-38S-MB-48-SS	250

GE – BT – LL





Male thread type **G:**

BSPT
(tapered)

Straight fitting

Sealing method: seal on tapered BSPT thread (PTFE tape or liquid anaerobic sealant)

Safety factor: **2,5:1**

series	D [mm]	M [mm]	G	galvanised steel		Zn-Ni zinc-plated steel		galvanised steel Guardian Seal®		AISI 316 stainless steel	
				index	P [bar]	index	P [bar]	index	P [bar]	index	P [bar]
LL	4	8x1	1/8”	HD-GE-04LL-BT-02	100	HD-GE-04LL-BT-02-CN	100	HD-GE-04LL-BT-02-W	100	HD-GE-04LL-BT-02-SS	100
	6	10x1	1/8”	HD-GE-06LL-BT-02	100	HD-GE-06LL-BT-02-CN	100	HD-GE-06LL-BT-02-W	100	HD-GE-06LL-BT-02-SS	100
	6	10x1	1/4”	-	-	HD-GE-06LL-BT-04-CN	100	-	-	HD-GE-06LL-BT-04-SS	100
	8	12x1	1/8”	HD-GE-08LL-BT-02	100	HD-GE-08LL-BT-02-CN	100	HD-GE-08LL-BT-02-W	100	HD-GE-08LL-BT-02-SS	100
	8	12x1	1/4”	-	-	HD-GE-08LL-BT-04-CN	100	-	-	HD-GE-08LL-BT-04-SS	100