DIN2353 fittings


RI - BB


Type F

Type E

Male thread type **G:** **BSP**







Reducer adaptor with BSP female thread

Sealing method: sealing lip
(metal - metal) - DIN 3852-**B**

Safety factor: **2,5:1**

type	L [mm]	G1 [BSP]	G2 [BSP]	galvanised steel		Zn-Ni zinc-plated steel		Guardian zinc-plated steel Seal®		AISI 316 stainless steel	
				index	P [bar]	index	P [bar]	index	P [bar]	index	P [bar]
F	31	1/8”	1/4”	-	-	HD-RI-02-04-BB-CN	630	-	-	HD-RI-02-04-BB-SS	630
F	32	1/8”	3/8”	-	-	HD-RI-02-06-BB-CN	630	-	-	HD-RI-02-06-BB-SS	630
F	30	1/4”	1/8”	-	-	HD-RI-04-02-BB-CN	630	-	-	HD-RI-04-02-BB-SS	630
F	36	1/4”	3/8”	-	-	HD-RI-04-06-BB-CN	630	-	-	HD-RI-04-06-BB-SS	630
F	40	1/4”	1/2”	-	-	HD-RI-04-08-BB-CN	630	-	-	HD-RI-04-08-BB-SS	630
F	43	1/4”	3/4”	-	-	HD-RI-04-12-BB-CN	630	-	-	HD-RI-04-12-BB-SS	630
E	22,5	3/8”	1/8”	-	-	HD-RI-06-02-BB-CN	630	-	-	HD-RI-06-02-BB-SS	630
F	36	3/8”	1/4”	-	-	HD-RI-06-04-BB-CN	630	-	-	HD-RI-06-04-BB-SS	400
F	41	3/8”	1/2”	-	-	HD-RI-06-08-BB-CN	630	-	-	HD-RI-06-08-BB-SS	400
F	44	3/8”	3/4”	-	-	HD-RI-06-12-BB-CN	400	-	-	HD-RI-06-12-BB-SS	400
E	24	1/2”	1/8”	-	-	HD-RI-08-02-BB-CN	630	-	-	HD-RI-08-02-BB-SS	630
E	24	1/2”	1/4”	-	-	HD-RI-08-04-BB-CN	630	-	-	HD-RI-08-04-BB-SS	630
F	36	1/2”	3/8”	-	-	HD-RI-08-06-BB-CN	630	-	-	HD-RI-08-06-BB-SS	400
F	46	1/2”	3/4”	-	-	HD-RI-08-12-BB-CN	630	-	-	HD-RI-08-12-BB-SS	400
F	49	1/2”	1”	-	-	HD-RI-08-16-BB-CN	400	-	-	HD-RI-08-16-BB-SS	400
F	53	1/2”	1.1/4”	-	-	HD-RI-08-20-BB-CN	400	-	-	HD-RI-08-20-BB-SS	250
E	26	3/4”	1/4”	-	-	HD-RI-12-04-BB-CN	400	-	-	HD-RI-12-04-BB-SS	400
E	26	3/4”	3/8”	-	-	HD-RI-12-06-BB-CN	400	-	-	HD-RI-12-06-BB-SS	400
F	41	3/4”	1/2”	-	-	HD-RI-12-08-BB-CN	400	-	-	HD-RI-12-08-BB-SS	400
F	51	3/4”	1”	-	-	HD-RI-12-16-BB-CN	400	-	-	HD-RI-12-16-BB-SS	400
F	55	3/4”	1.1/4”	-	-	HD-RI-12-20-BB-CN	400	-	-	HD-RI-12-20-BB-SS	250
F	57	3/4”	1.1/2”	-	-	HD-RI-12-24-BB-CN	315	-	-	HD-RI-12-24-BB-SS	250
E	29	1”	1/4”	-	-	HD-RI-16-04-BB-CN	400	-	-	HD-RI-16-04-BB-SS	400
E	29	1”	3/8”	-	-	HD-RI-16-06-BB-CN	400	-	-	HD-RI-16-06-BB-SS	400
E	29	1”	1/2”	-	-	HD-RI-16-08-BB-CN	400	-	-	HD-RI-16-08-BB-SS	400
F	47	1”	3/4”	-	-	HD-RI-16-12-BB-CN	400	-	-	HD-RI-16-12-BB-SS	400
F	57	1”	1.1/4”	-	-	HD-RI-16-20-BB-CN	400	-	-	HD-RI-16-20-BB-SS	250
F	59	1”	1.1/2”	-	-	HD-RI-16-24-BB-CN	315	-	-	HD-RI-16-24-BB-SS	250
E	32	1.1/4”	1/2”	-	-	HD-RI-20-08-BB-CN	400	-	-	HD-RI-20-08-BB-SS	400
E	32	1.1/4”	3/4”	-	-	HD-RI-20-12-BB-CN	400	-	-	HD-RI-20-12-BB-SS	400
F	52	1.1/4”	1”	-	-	HD-RI-20-16-BB-CN	400	-	-	HD-RI-20-16-BB-SS	250
F	60	1.1/4”	1.1/2”	-	-	HD-RI-20-24-BB-CN	315	-	-	HD-RI-20-24-BB-SS	250
E	36	1.1/2”	1/2”	-	-	HD-RI-24-08-BB-CN	315	-	-	HD-RI-24-08-BB-SS	315
E	36	1.1/2”	3/4”	-	-	HD-RI-24-12-BB-CN	315	-	-	HD-RI-24-12-BB-SS	315
E	36	1.1/2”	1”	-	-	HD-RI-24-16-BB-CN	315	-	-	HD-RI-24-16-BB-SS	315
F	58	1.1/2”	1.1/4”	-	-	HD-RI-24-20-BB-CN	315	-	-	HD-RI-24-20-BB-SS	250